

Takeoff weight about 1868 lbs.
 Airport elevation about 1536 ft msl
 Airport temperature about 97°F

TAKE-OFF DATA

TAKE-OFF DISTANCE FROM HARD SURFACE RUNWAY , FLAPS UP

GROSS WEIGHT LBS.	IAS AT 50 FT. MPH	HEAD WIND KNOTS	@ S.L. & 59° F		@ 2500 ft. & 50° F		@ 5000 ft. & 41° F		@ 7500 ft. & 32° F	
			GROUND RUN	TOTAL TO CLEAR 50' OBS.	GROUND RUN	TOTAL TO CLEAR 50' OBS.	GROUND RUN	TOTAL TO CLEAR 50' OBS.	GROUND RUN	TOTAL TO CLEAR 50' OBS.
1700	60	0	435	780	520	920	625	1095	765	1370
		10	290	570	355	680	430	820	535	1040
		20	175	385	215	470	270	575	345	745
2000	65	0	630	1095	755	1325	905	1625	1120	2155
		10	435	820	530	1005	645	1250	810	1685
		20	275	580	340	720	425	910	595	1255
2300	70	0	885	1525	1040	1910	1255	2480	1565	3855
		10	615	1170	750	1485	920	1955	1160	3110
		20	405	850	505	1100	630	1480	810	2425

Note: Increase distance 10% for each 25°F above standard temperature for particular altitude.

MAXIMUM RATE-OF-CLIMB DATA

GROSS WEIGHT LBS.	@ S.L. & 59° F			@ 5000 ft. & 41° F			@ 10,000 ft. & 23° F			@ 15,000 ft. & 5° F		
	IAS MPH	RATE OF CLIMB FT/MIN.	GALS OF FUEL USED	IAS MPH	RATE OF CLIMB FT/MIN.	FROM S.L. FUEL USED	IAS MPH	RATE OF CLIMB FT/MIN.	FROM S.L. FUEL USED	IAS MPH	RATE OF CLIMB FT/MIN.	FROM S.L. FUEL USED
1700	75	1085	1.0	73	825	1.9	71	570	2.9	70	315	4.4
2000	77	840	1.0	76	610	2.2	74	380	3.6	73	155	6.3
2300	80	645	1.0	78	435	2.6	77	230	4.8	76	22	11.5

Note: Flaps up, full throttle and mixture leaned for smooth operation above 5000 ft.
 Fuel used includes warm-up and take-off allowance.

Figure 5-3.