

CESSNA 402C QRH
COCKPIT CHECKLIST

23 JAN 2009

BEFORE STARTING ENGINES

1. Preflight Complete
2. Cabin Door Secured
3. Passenger Briefing Complete
4. Crossfeed Shutoff Open
5. Fuel Selectors Main Tanks
6. Cowl Flaps Open & Locked
7. Wing Flaps Verify Up
8. Mixtures Full Rich
9. Propellers Full Forward
10. Throttles Full Forward
11. Landing Gear Handle Down
12. Control Lock Remove
13. Alternate Air Controls In and Locked
14. Switches & Circuit Breakers Checked
15. Propeller Area Cleared
16. Battery and Alternators On
17. Magnetos On
18. Gear Down Lights Check 3 Green
19. Annunciator Checked
20. Fuel Quantity Checked
21. Lights As Required

BEFORE TAKEOFF

1. Crossfeed Shutoff Open
2. Fuel Selectors Main Tanks (Feel for Detent)
3. Cowl Flaps Open & Locked
4. Autopilot Check & Set
5. Trim Tabs Set
6. Wing Flaps Up
7. Mixtures Full Rich
8. Propellers Full Forward
9. Fuel Quantity Check
10. Engine Instruments Check
11. Radios Check & Set
12. Radar As Required
13. Cylinder Head Temperature >150 degrees
14. *Engine Runup Complete*
15. Cylinder Head Temperature >200 degrees
16. Circuit Breakers Check
17. Alternate Air Controls Check
18. Flight Controls Check
19. Anti-Ice/De-Ice As Required
20. Crew Door Lock
21. Parking Brake Released

(Over) →

CESSNA 402C QRH
COCKPIT CHECKLIST

Engine Run-up Checks as follows

- Throttles 1700 RPM
- Cycle Props
- Hydraulic Flow lights out
- Starter Warning lights out
- Suction in the green
- Check Magnetos
- Auxiliary Fuel Pumps low
- Check Voltammeter
- De-ice equipment check
- Throttles below 1000 RPM

CRUISE

1. Cruise Power..... Set
2. Mixtures..... As Required
3. Cowl Flaps As Required
4. Fuel Selectors Main Tanks (Feel for Detent)
5. Propellers..... Synchronize Manually

BEFORE LANDING

1. Landing Gear Handle..... Down
2. Mixtures..... Full Rich
3. Propellers..... As Required
4. Gear Down Lights 3 Green, Unlock light - off
5. Switches..... As Required
6. Approach Speed 120 KIAS
7. Wing Flaps 0-45 Degrees
8. Landing Speed..... Proper for Weight

AFTER LANDING

1. Cowl Flaps..... Open
2. Wing Flaps Up
3. Transponder..... Standby
4. Radar Standby
5. Auxiliary Fuel Pumps Low
6. Lights As Required
7. Heater As Required

SHUTDOWN

1. Accessories..... Off
2. Auxiliary Fuel Pumps Off
3. Mixtures..... IDLE CUT-OFF
4. Magnetos Off (Gang Bar)
5. Battery/Alternators Off (Gang Bar)
6. Parking Brake..... As Required
7. Control Gust Lock Install
8. Crew Door..... Unlock

23 JAN 2009