

# Aircraft Record General Information

Manufacturer CESSNA Model 172N  
Serial 17270186 Registration Number N738RV  
Date of Manufacture 10/77

## Engine(s) currently installed:

Manufacturer LYCOMING Model O-320-H2AD Serial L-3171-76  
Manufacturer \_\_\_\_\_ Model \_\_\_\_\_ Serial \_\_\_\_\_

## Propeller(s) currently installed:

Manufacturer \_\_\_\_\_ Model \_\_\_\_\_  
HUB Model \_\_\_\_\_ Serial \_\_\_\_\_ Serial \_\_\_\_\_  
Blade Model \_\_\_\_\_ Serial \_\_\_\_\_ Serial \_\_\_\_\_ Serial \_\_\_\_\_  
Blade Model \_\_\_\_\_ Serial \_\_\_\_\_ Serial \_\_\_\_\_ Serial \_\_\_\_\_

| DATE<br>19__ | RECORDING<br>TACH<br>TIME | TODAYS<br>FLIGHT | TOTAL<br>TIME IN<br>SERVICE | Description of Inspections, Tests, Repairs and Alterations<br>Entries must be endorsed with Name, Rating and Certificate Number of<br>Technician or Repair Facility. (See back pages for other specific entries.) |
|--------------|---------------------------|------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1-28-10      |                           |                  |                             | -C/W Annual Inspection of                                                                                                                                                                                         |
| Tach         | 419.5                     |                  |                             | Ceifrano C/W EIT function check                                                                                                                                                                                   |
| ACTI         | <del>415.8</del>          |                  |                             | DDW 71.20 TD C/W AD 87-20-03 Rev 2                                                                                                                                                                                |
|              | 3753.8                    |                  |                             | Set rails & seal ass. next due Tach                                                                                                                                                                               |
|              |                           |                  |                             | 519.5. Installed new Conda 6.00X6.0                                                                                                                                                                               |
|              |                           |                  |                             | ties 24 & LH positions installed new                                                                                                                                                                              |
|              |                           |                  |                             | 5.00X5.0 nose tie. cleaned and lubed                                                                                                                                                                              |
|              |                           |                  |                             | wheel bearings. Installed new o-rings                                                                                                                                                                             |
|              |                           |                  |                             | primer. Installed new center hard                                                                                                                                                                                 |
|              |                           |                  |                             | control PIN 51230-17. Installed new                                                                                                                                                                               |
|              |                           |                  |                             | stroke life Switch PIN 52160-1. Disassembled                                                                                                                                                                      |
|              |                           |                  |                             | nose strut, cleaned and re-sealed with                                                                                                                                                                            |
|              |                           |                  |                             | Strut kit PIN JMCN31. serviced with                                                                                                                                                                               |
|              |                           |                  |                             | 5600 hydraulic fluid and nitrogen. Disassembled                                                                                                                                                                   |
|              |                           |                  |                             | nose gear steering clasper, installed new                                                                                                                                                                         |
|              |                           |                  |                             | O-rings. ms25775-011 & -213. 5600 fluid.                                                                                                                                                                          |
|              |                           |                  |                             | installed with new hardware. Installed                                                                                                                                                                            |

