DESCRIPTIVE DATA

NOTE

M-1285 thru M-2178 are 14-volt systems. The battery switch is placarded BATTERY & ALT and the alternator switch is placarded ALT (or ALT FIELD). 28-volt systems, M-2179 and after, are placarded BATTERY for the battery switch and ALT FIELD for the alternator switch. All items throughout this handbook that refer to battery switch refer to either BATTERY & ALT switch or BATTERY switch depending upon configuration.

ENGINE

Airplane is equipped with an Avco Lycoming O-360-A2G, O-360-A4G, O-360-A4J or O-360-A4K engine rated at 180 horsepower.

Take-off and maximum continuous operation (sea level): 2700 rpm, full throttle.

Engine cooling has been demonstrated for a 100° F day.

PROPELLER

Sensenich M76EMMS-0-60 or 76EM8S5-0-60 fixed pitch, two blade propeller. Static rpm at maximum permissible throttle settings: Not over 2350 rpm and not under 2250 rpm. No additional tolerance permitted.

FUEL

Aviation Gasoline 91/96 (blue) minimum grade or 100 (green) or 100LL (blue).

M-1285 thru M-1516:

*59.8-gallon system

(29.9 gallons each tank) *58 gallons usable

Each tank has provisions for partial filling to:

20 gallons each tank 38.2 gallons usable 15 gallons each tank 28.2 gallons usable

Revised: April 1979

BEECHCRAFT Sundowner 180 C23 (M-1285 and After)

Section II Limitations

FUEL QUANTITY

| | M-1517 thru M-1879 except M-1875, | | rior | air- |
|------|---|------|------|------|
| plan | es after compliance with S.I. No. 0624- | 281 | | |
| ` | Yellow Band | E to | 3/8 | full |
| | M-1875, M-1880 and after Yellow Band | E to | 1/3 | full |

WEIGHT LIMITS

NORMAL CATEGORY

| Maximum Ramp Weight | 2455 lbs |
|----------------------------------|------------|
| and Landing Weight | 2450 lbs |
| Zero Fuel Weight No Structural I | Limitation |
| Maximum Baggage Compartment | |
| Load | 270 lbs |
| UTILITY/ACROBATIC CATEGORY | |
| | |

| waximum Ramp Weight | 2035 IDS |
|------------------------------|----------------------------|
| Maximum Take-off | |
| and Landing Weight | |
| Zero Fuel Weight | . No Structural Limitation |
| Maximum Baggage Compartment | |
| Load (Utility Category Only) | |

CENTER OF GRAVITY LIMITS

NORMAL CATEGORY

Forward: 107.8 inches aft of datum to 1800 lbs with straight line variation to 114.5 inches at 2450 lbs.

118.3 inches aft of datum at all weights. Aft: