## DOCKET No.: SA-521 EXHIBIT No. 17PP

## NATIONAL TRANSPORTATION SAFETY BOARD WASHINGTON, D.C.

FAR 121.371 – Required Inspection Personnel

(1 page)

(11) For all models of the Lockheed L-1011, the flight cycle implementation time is 27,000 flights.

(12) For the Fokker F-28 Mark 1000, 2000, 3000, and 4000, the flight cycle implementation time is 60,000 flights.

## {New-2001-6 (b) added May 7, 2001, effective June 6, 2001}

(b) After June 7, 2004, no certificate holder may operate a turbine-powered transport category airplane with a type certificate issued after January 1, 1958, and either a maximum type certificated passenger capacity of 30 or more, or a maximum type certificated payload capacity of 7,500 pounds or more, unless instructions for maintenance and inspection of the fuel tank system are incorporated in its maintenance program. These instructions must address the actual configuration of the fuel tank systems of each affected airplane and must be approved by the FAA Aircraft Certification Office (ACO), or office of the Transport Airplane Directorate, having cognizance over the type certificate for the affected airplane. Operators must submit their request through an appropriate FAA Principal Maintenance Inspector, who may add comments and then send it to the manager of the FAA Aircraft Certification Office of the FAA Aircraft Certificate for the affected airplane. Operators can be revised only with the approval of the FAA Aircraft Certification Office of the Transport Airplane Directorate, having cognizance over the type certificate for the affected airplane. Aircraft Airplane Directorate, having cognizance over the type certificate for the affected airplane. Aircraft Airplane Directorate, having cognizance over the type certificate for the affected airplane. Aircraft Airplane Directorate, having cognizance over the type certificate for the affected airplane. Operators must submit their requests for revisions through an appropriate FAA Principal Maintenance Inspector, who may add comments and then send it to the manager of the affected airplane. Operators must submit their requests for revisions through an appropriate FAA Principal Maintenance Inspector, who may add comments and then send it to the manager of the appropriate office.

[Amdt. 121-275, 65 FR 24108, April 25, 2000, effective May 25, 2000, as corrected at 65 FR 50744, August 21, 2000; Amdt. 121-282, 66 FR 23085, May 7, 2001, effective June 6, 2001]

## § 121.371 Required inspection personnel.

(a) No person may use any person to perform required inspections unless the person performing the inspection is appropriately certificated, properly trained, qualified, and authorized to do so.

(b) No person may allow any person to perform a required inspection unless, at that time, the person performing that inspection is under the supervision and control of an inspection unit.

(c) No person may perform a required inspection if he performed the item of work required to be inspected.

(d) Each certificated holder shall maintain, or shall determine that each person with whom it arranges to perform its required inspections maintains, a current listing of persons who have been trained, qualified, and authorized to conduct required inspections. The persons must be identified by name, occupational title, and the inspections that they are authorized to perform. The certificated holder (or person with whom it arranges to perform its required inspections) shall give written information to each person so authorized describing the extent of his responsibilities authorities, and inspectional limitations. The list shall be made available for inspection by the Administrator upon request.