

DOCUMENT CONTROL SHEET

BOMBARDIER
the evolution of mobility

UNIT#
211

INSPECTION TYPE: **6M**

pick from drop
down list

DATE IN:	12/30/2014
FINISHED:	1/5/2015

WORK ORDER # ECMS02 2015

RECEIVED JAN 09 2015

RECENT WHEEL MEASUREMENTS

Wheel #	Flange Ht.	Flange Th.	Rim Th.
1	17	0	40
2	17	0	40
3	17	0	40
4	17	0	40
5	17	0	40
6	17	0	40
7	17	0	40
8	17	0	40

RECENT DEFECTS TO INSPECT

CAPITAL PROJECTS COMPLETED

VESTIBULE CURTAINS INSTALLED CORRECTLY & GOOD CONDITION

DATE

YES

1/5

ALL TASK ITEMS SIGNED OFF

WHEEL DATA ATTACHED

DATE

YES

1/5

HORN TEST COPY ATTACHED (*)

N/A

EVENT RECORDER DOWNLOAD AND HARD COPY ATTACHED (*)

N/A

ATS DOCUMENTATION AVAILABLE (*)

N/A

WINDOW PULL TEST DATA ATTACHED

1/5

SUPERVISOR SIGN OFF: 

DATE: 1/5/15

(*) Required for locomotives & cab cars

REVIEWED BY: 

DATE: 1/7/15

Report Date/Time: 12/30/2014 10:34
GARMANE

User:

PM ORDER



Work Order ECMS02-2014-1426

Work Order ECMS02-2014-1426
Opened by: GARMANE

Datetime In 12/30/2014 10:32
Datetime Due 12/30/2014 11:02
Est Complete

Current Life
Meter 1 0
Meter 2 0
Priority 1 30 MINUTES
Employee ID

Parking Stall
Reference Order

Account ID 100000-1.16.55-50421 SHOP OPERATIONS
Tax Code
Est Hours 0.00

Equipment ID SCAX211 OWNED
2010 ROTEM COACH STAINLESS
License No
Serial No NA SCAX211
In Service 12/13/2010
PM Class COACH
COACH
Dept 2300
EQUIPMENT MAINTENANCE
Asset ID
Contact

Warranty Exp Date 08/27/2012
Equip Status
Hat Number



Leave Work Order


PM Service 180C-CC

Assigned Shop ECMS02

No next PM service info: this PM order is for an inspection

Comments

Notes



Report Date/Time: 12/30/2014 10:50
GARMANE

User:

REPAIR ORDER



Work Order ECMS02-2014-1427

Work Order ECMS02-2014-1427
Opened by: GARMANE

Equipment ID SCAX211 OWNED
2010 ROTEM COACH STAINLESS

License No

Datetime In 12/30/2014 10:49

Serial No NA SCAX211

Datetime Due 12/30/2014 11:19

In Service 12/13/2010

Est Complete

Maint Class COACH

Current Life

COACH

Meter 1 0

Dept 2300

Meter 2 0

EQUIPMENT MAINTENANCE

Priority 1 30 MINUTES

Asset ID

Employee ID

Contact

Parking Stall

Warranty Exp Date 08/27/2012

Reference Order

Equip Status

Account ID 100000-1.16.55-50421 SHOP OPERATIONS

Tax Code

Hat Number

Est Hours 0.00



Leave Work Order

Repair Reason WN WORN

Work Class 1 Warranty NO

Comments

Notes

-- 12/30/2014 10:50 - GARMANE - EUGENE GARMAN --

REPAIR WORK ORDER

1/5/15

DOCUMENT CONTROL SHEET

INSPECTOR INITIALS	MECHANICAL / ELECTRICAL DEFECTS		EQUIP
			211
			6MONTH PM
	DEFECT ONE PER BOX	CORRECTIVE ACTION	SRD# + INITIALS
ML	wheels #1 and #2 have flat spots	wheels true	ML
KB	Panel door Nut missing from roller	put bolt on	KB
KB	Headrest hand hold loose	tighten up	
KB	120 volt wall plug cover broken	nig	KB
KB	emergency window board	Replaced whole board	
/			

SUPERVISOR: [REDACTED]

DATE: 1/15/15

Signature of Supervisor denotes that supervisor has reviewed the defects above and has ensured each defect has been addressed and the appropriate corrective action has been entered, as well as the initial of the employee performing or inspecting the work

INSPECTOR INITIALS	MECHANICAL / ELECTRICAL DEFECTS		EQUIP
			211
			6MONTH PM
	DEFECT ONE PER BOX	CORRECTIVE ACTION	SRD# + INITIALS
KB	At seat of window molding Torn	OK For Service	SI
KB	First Aid missing Manual	NIS	la
KB	Ceiling trim loose	pushed trim back in place	la
KB	Emergency window decals Faded and or peeling	Replaced with new ones	la
KB	Warning do not place arm decals at doors faded	Replaced with new ones	la
KB	Open door in emergency Pull Ring decals peeling	Replaced with new ones	la
KB	Hardtail screw loose	tightened up	la
KB	480 decal peeling	Replaced with new one	la
KB	Danger High Voltage Graffiti on Headrest	replaced	la

SUPERVISOR



DATE:




1/5/15

Signature of Supervisor denotes that supervisor has reviewed the defects above and has ensured each defect has been addressed and the appropriate corrective action has been entered, as well as the initial of the employee performing or inspecting the work

METROLINK/180 DAY INSPECTION COACH/CAB CAR

Work Order Number: 1426

Date Work Order Opened: 12/30/14

<u>Task ID</u>	<u>Description</u>	<u>Completed by:</u>
	<u>CAR SERVICING</u>	
C-C 101 SRT-60"	<p>Dump, sanitize, service and water car.</p> <p>Empty and sanitize toilet retention tank.</p> <p>*1. Open wheel skirts at BL corner.</p> <p>2. Remove cap from the 1" water-intake pipe.</p> <p>3. Remove cap from the 3" ball valve and connect dumping hose to ball valve.</p> <p>4. Open ball valve dumping contents in holding tank into sewer.</p> <p>5. Connect jet-fog nozzle to the 1" water intake pipe and connect a fresh water hose to the other end of the jet-fog nozzle.</p> <p>6. Open water supply allowing water to flow into water-intake tank for 5 to 10 minutes.</p> <p>7. Close ball valve.</p> <p>8. To remove large solid object from waste holding tank, remove hexagon nuts to remove the flange plate and gasket to gain access to holding tank..</p> <p>9. Pour 1/2 gallon of bleach down toilet and flush.</p> <p>10. Open outside water supply and fill waste-holding tank until water reaches top of flapper.</p> <p>11. Allow water in waste holding tank to stand for 30 minutes.</p> <p>12. Open ball valve allowing contents to drain into sewer.</p> <p>13. Close ball valve, disconnect dump hose from ball valve, and install cap onto ball valve with cam locks locked. Ensure chain is attached to the cap and secured to the car.</p> <p>14. Remove jet-fog nozzle from 1" water intake pipe, disconnect hose, and reinstall cap onto water-intake pipe.</p> <p>*15. Close and latch wheel skirts.</p> <p>Sanitize and fill potable water tanks.</p> <p>*1. Open wheel skirts at BL corner.</p> <p>2. Remove protective cap and connect bleach-filling adaptor to the water-fill connection and connect fresh-water hose to the other end of the adaptor..</p> <p>3. In plumbing compartment, open drains valves and drain tanks to approximately 1/2 full. (Drain pipes are located adjacent to jet-fog nozzle.)</p> <p>4. Pour 1/4 gallon of bleach into bleach-filling adaptor.</p> <p>5. Fill both water tanks to capacity.</p> <p>*6. Close pressurization valve by turning:</p> <ul style="list-style-type: none">a) the air cut-off valve to the close position.b) the overflow vent valve to the open position. <p>7. Allow 30 minutes for adequate sanitation.</p> <p>8. Drain and flush tanks until proper "pH" level has been reached.</p> <ul style="list-style-type: none">a) test water using white color "pH" testing paper at drinking fountainb) Proper "pH" level is reached when white test paper turns to a light gray. <p>9. After proper "pH" level is reached, close drain valves for the water tanks.</p> <p>10. Disconnect bleach-filling adaptor. Apply the protective cap ensuring it is properly secured.</p> <p>*11. Open the air cut-off valve and close the overflow vent valve.</p> <p>*12. Close and latch wheel skirts.</p> <p>Replenish biocide disinfectant.</p> <p>Connect a rubber hose to the drain/vent connection placing opposite end of hose in a 5 gallon container beneath overflow outlet. Connect quick disconnect fitting to biocide fill connection and fill the 20 gallon tank. When full, solution will pour out of the biocide drain/vent connection. Set biocide counter, located in plumbing compartment to zero.</p> <p>² Applies to Bombardier Vehicles only.</p>	  

Task ID Description

Under Frame Inspection

C-C 102
SRT-30"

Inspect couplers, draft gears, knuckles, cabling and hoses.

Inspect condition of uncoupling lever and brackets.

Ensure uncoupling lever is not cracked, broken or bent and operate as intended. Close knuckle and operate uncoupling lever and check that the lever rotates the rotary lock lift lever, which opens the lock and knuckle. Inspect for loose or missing hardware securing uncoupling lever brackets.

Inspect & gauge knuckle, coupler and check slack.

Gauge coupler, checking, Guard Arm Distortion, Contour Wear, Knuckle Nose and Knuckle Stretch. Draft gear components, pocket and coupler pin must be inspected for slack or wear. Using a long bar between the coupler horn and striker face and prying outward, measure the distance between the coupler horn and the striker face. Then move the coupler in as far as possible towards the draft gear and again measure the distance between the coupler horn and the striker face. The distance between the two is the amount of free slack in the draft gear and coupler arrangement. Total slack must not exceed 1/2". Check anti-creep protection.

Total slack Front 0 Rear 0

Check & record coupler height.

Check and record the following measurements:

	Front	Rear	Clearance Limits
Coupler Height Above Top of Rail	<u>33</u>	<u>33 1/2</u>	31-1/2" Min. 34-1/2" Max.

Ensure coupler maintained in a level position. Check coupler bounce. Excessive couple bounce and coupler carrier ears not in contact with coupler pocket stop blocks indicate weak or broken coupler carrier springs. Replace worn coupler carrier ears and stop blocks if groove is worn into bottom of block.

Inspect draft gear, yoke, coupler & coupler carrier.

Inspect coupler body and parts, yokes, and connections for cracks, broken or missing parts. Replace coupler if cracking is found in the pin protector boss or pivot lug, or if portion of the pin protector boss are missing or broken. To ensure proper locking of coupler, check for the presence of an inverted U-shaped notch located in the lower edge of both side walls of the lock hole shroud. When this recess is clear and unobstructed, the knuckle is properly locked. Inspect draft gear for signs of separation from its substrate or any signs of surface cuts or splits. Separations, cuts, or splits may not exceed 1-1/2 inches in length and 3/4 inch in depth. Check for slack in the rubber pad assembly indicating draft gear is loose in the pocket. Replace the yoke bushings if the inside diameters are worn to 3-3/16 inch.

Inspect MU and communication cables and receptacles.

Inspect condition of MU and communication cables. Inspect condition of insulation and for signs of a stretched cable. Ensure covers are not missing, broken or cracked, are spring loaded and operate properly. Check for broken receptacle pins. Check the mica insulating plate for cracks and mounting hardware in place and secure. Inspect for dirt/moisture contamination. Remove dirt and debris using air pressure using an electrical cleaner if needed.

Inspect HEP cables, receptacles and 480V decals.


Inspect HEP cables for cracks, cuts, damaged insulation or signs of a stretched cable. Check for broken, flashed or partially missing pins. Ensure covers are not missing, broken, cracked and are functioning properly. Ensure "DANGER" - 480 Volt" or Danger - High Voltage decals are in place at each HEP receptacle and are legible.


Inspect train line hoses, piping and valves.

Inspect brake pipe and main reservoir hoses for cuts, debris damage, or evidence of being collapsed. Inspect condition of glad-hand and gasket.

Ensure dummy couplings are not damaged and secured to the car. Attach free end air hose to dummy coupling.

Inspect angle valves and end valves for damage. Make sure handles are not bent or broke spring is in place and effective, and the stops prevent movement of handle in the open position.





Task ID Description

**C-C 103
SRT-30"**

Inspect battery box, record specific gravity, service batteries.

Inspect battery compartment and switch box.
Inspect battery compartment and cover for damage, Ensure locking devices are in place and are effective. Apply battery compartment cover and secure with hardware. Inspect switch box, cover and latches. Clean battery switch box, install the fuses in the fuse holder and place the battery switch in the on position.

Check and record specific gravity of each battery cell.

Left Side Battery Box			Right Side Battery Box		
Cell No.	Cell No.	Cell No.	Cell No.	Cell No.	Cell No.
1 1.21	9 1.24	17 1.22	1 1.24	9 1.21	17 1.21
2 1.22	10 1.22	18 1.22	2 1.24	10 1.23	18 1.21
3 1.23	11 1.21	19 1.21	3 1.23	11 1.21	19 1.2
4 1.21	12 1.22	20 1.23	4 1.23	12 1.24	20 1.25
5 1.21	13 1.22	21 1.22	5 1.23	13 1.24	21 1.24
6 1.21	14 1.22	22 1.22	6 1.23	14 1.25	22 1.23
7 1.22	15 1.23	23 1.21	7 1.21	15 1.25	23 1.24
8 1.22	16 1.21	24 1.21	8 1.21	16 1.21	24 1.25

Facing Battery

Note: If distilled water has been added before check specific gravity, charge the batteries for a minimum of five (5) hours.

If the specific gravity is less than 1.15, replace battery.

After checking specific gravity, turn on as many low voltage load as possible (lights, open doors at door stations, headlights, etc.) Turn off the battery charger main breaker. Allow batteries to discharge for ten (10) minutes and check the voltage drop across each cell on car nos. 183-210, and each pair of cells on all other cars. If the voltage drops to a value lower than one (1) volt on any of the cells, replace the battery with the low cell.

Clean battery boxes and exterior of battery sets.

Place the battery switch in the off position and open the battery switch box and remove both fuses from the fuse holder. Open the battery boxes and extend the battery trays completely. Do not use abrasive cleansers, wire brushes, or acid washes inside the battery compartments. Using clean water and a noncorrosive, non-caustic cleansing agent, wash the interior of the battery boxes and the exterior of the battery set.

Inspect battery & fluid level, add de-ionized water if needed.

Visually check batteries for cracks. Battery should be tight in tray with blocking in place. Inspect cables, terminals, connectors and terminal bars. Excessive water consumption indicates too high a charging voltage and little or no water consumption indicates that a battery is being inadequately charged. The electrolyte levels are visible through the plastic containers of the cells and have upper and lower lines on the containers to indicate the maximum and minimum levels. The cells need to be topped-up with distilled or de-ionized water when the electrolyte level is midway between the lower and upper line. Avoid leaks and spills. Note: An electrolyte spill can be neutralized with baking soda. Flush area with large amounts of fresh water once neutralized.

Coat battery terminals and lubricate battery tray rails.

With battery terminal wires and jumper bars disconnected, use clean water, a soft bristle brush and noncorrosive, non-caustic cleansing agent to clean all connections. Coat all terminals using Nifecote or a suitable approved substitute. Install jumper bars and connect battery terminal wires. Lubricate rails on the battery tray and ensure trolley moves freely.

Task ID
C-C 104
SRT-30"

Description
Inspect wheels and record wheel measurements.

Completed by:



Inspect wheels for defects.

Following are condemning conditions involving wheels. Report any defective condition found to your supervisor regardless of severity.

Flat spots	A single flat spot that is 2-1/2 inches or more in length, or two adjoining spots that are each two or more inches in length.
Gouge or chip in the flange	Gouge or chip that is more than 1-1/2 inches in length and 1/2 inch in width.
Broken rim	If the tread, measured from the flange at a point 5/8 of an inch above the tread, is less than 3-3/4 inches in width.
Shelling	A shelled-out spot 2-1/2 inches or more in length, or two adjoining spots that are each two or more inches in length.
Seam running lengthwise	A seam running lengthwise that is within 3-3/4 inches of the flange.
Tread worn hollow	A tread worn hollow 5/16 of an inch or more.
Crack or break	A crack or break in the flange, tread, rim, plate, or hub.
Loose wheel	Any indication the wheel may be loose. Look for rust where the axle contacts the hub.

Remove old torque seal and apply fresh torque seal extending from wheel hub to outside axle face.

CAR 211

Record wheel measurements.

	Flange Ht.	Flange Th.	Rim Th.
Go-No-Go Gauge	Max. 1-1/2"	Min. 1"	Min. 1"
Finger Gauge Readings	24	8	16

Serial Number

Wheel No.1	<u>18</u>	<u>0</u>	<u>42</u>	<u>100947</u>
Wheel No.2	<u>18</u>	<u>0</u>	<u>42</u>	<u>100995</u>
Wheel No. 3	<u>18</u>	<u>0</u>	<u>42</u>	<u>101011</u>
Wheel No. 4	<u>18</u>	<u>0</u>	<u>42</u>	<u>100992</u>
Wheel No. 5	<u>18</u>	<u>0</u>	<u>42</u>	<u>100999</u>
Wheel No. 6	<u>18</u>	<u>0</u>	<u>42</u>	<u>101010</u>
Wheel No. 7	<u>18</u>	<u>0</u>	<u>42</u>	<u>100938</u>
Wheel No. 8	<u>18</u>	<u>0</u>	<u>42</u>	<u>101014</u>

Action Taken:


- Wheels Trued
- Changed Wheels
- OK For Service

Notify Supervisor if readings are at these points:

Flange Ht.	Flange Th.	Rim Th.
22	5	18



Reviewed by Supervisor



Task ID
C-C 105
SRT-30"

Description

Inspect tread and disc brake units, record disc measurements.

Inspect tread brake units and brake shoes.

Inspect for loose or missing hardware. Lubricate the hanger and brake head bolts. Lubricant Tread brake reservoir of the body is to be filled with lithium molybdenum disulfide-bas grease (WABCO M-7672-01).

Inspect disc brake units and check fluid level.

Inspect for loose or missing hardware and signs of rust. Air leaks at disc brake unit must be corrected. With the brakes released, check for any apparent brake fluid leaks around the disc brake unit reservoir castings.

Check disc brake fluid level:

- a) Insert a bar or lever between the tongs and retract the piston push rod all the way back. Block in this position.
- b) Remove dirt and completely clean top cover before removing.
- c) Loosen four bolts and remove the top cover, being careful not to contaminate the fluid with foreign material.
- d) If the screen can be seen above the fluid level, add clean Dow Corning Silicone Brake Fluid No. Q2-1141, from a clean container so the fluid level is 1/4 inch below the top of the reservoir.

Disc Brake Fluid Added: Yes No

NOTE: If fluid is added more than twice a year, the actuator is malfunctioning and requires replacement.

Lubricate swivel pin and bushing with lithium molybdenum disulfide-base grease (WABCO M-7672-1). Use a grease gun on the swivel bracket grease fitting.

Inspect and record brake disc measurements.

Renew disc:

- a) if surface cracks are more than 2-1/2 inches long (either side) or are within 3/8 in of the outer edge.
- b) if the disc shows any score marks or there are any protrusions.
- c) if there are nicks on the outer edge of the disc longer than 3/4 inch wide radially.
- d) if there are cracks in the hub.

Ensure the bolts securing the disc are not loose, broken or missing and the locking tabs are in place and properly bent to prevent movement of the bolt. Cracks in the torque seal may indicate bolt movement.


Renew disc if the thickness of the disc (face to face) is less than 3.34 inches thick, or if the thickness of an individual face is less than .665 in.

Remove old torque seal and apply fresh torque seal to each bolt that extends from bolt head to disc hub.

Take three (3) measurements approximately 120 degrees apart and 2-1/2" in from the disc edge.

Task ID Description

Record Brake Disc Measurements



Disc Wheel 1

Axle Serial No. A167

	1st	2nd	3rd	Smallest Value
Outside Wall Thickness	0.904	0.917	0.920	0.904
Inside Wall Thickness	0.948	0.973	0.971	0.948
Face-to-Face	3.734	3.742	3.735	3.734

Disc Renewed
 Yes _____ No

Disc Wheel 2

Axle Serial No. A167

	1st	2nd	3rd	Smallest Value
Outside Wall Thickness	0.921	0.916	0.903	0.903
Inside Wall Thickness	0.951	0.960	0.959	0.951
Face-to-Face	3.729	3.738	3.748	3.729

Disc Renewed
 Yes _____ No

Disc Wheel 3

Axle Serial No. LA125

	1st	2nd	3rd	Smallest Value
Outside Wall Thickness	0.903	0.957	0.899	0.899
Inside Wall Thickness	0.939	0.947	0.946	0.939
Face-to-Face	3.743	3.735	3.727	3.727

Disc Renewed
 Yes _____ No

Disc Wheel 4

Axle Serial No. LA125

	1st	2nd	3rd	Smallest Value
Outside Wall Thickness	0.903	0.911	0.909	0.903
Inside Wall Thickness	0.952	0.957	0.956	0.952
Face-to-Face	3.743	3.737	3.735	3.737

Disc Renewed
 Yes _____ No

Disc Wheel 5

Axle Serial No. SQ71

	1st	2nd	3rd	Smallest Value
Outside Wall Thickness	0.909	0.909	0.907	0.907
Inside Wall Thickness	0.958	0.953	0.951	0.951
Face-to-Face	3.740	3.806	3.760	3.740

Disc Renewed
 Yes _____ No

Disc Wheel 6

Axle Serial No. SQ71

	1st	2nd	3rd	Smallest Value
Outside Wall Thickness	0.948	0.940	0.980	0.940
Inside Wall Thickness	0.939	0.964	0.949	0.939
Face-to-Face	3.733	3.749	3.735	3.735

Disc Renewed
 Yes _____ No

Disc Wheel 7

Axle Serial No. 799

	1st	2nd	3rd	Smallest Value
Outside Wall Thickness	0.948	0.917	0.930	0.917
Inside Wall Thickness	0.940	0.939	0.944	0.939
Face-to-Face	3.740	3.736	3.729	3.729

Disc Renewed
 Yes _____ No

Task ID **Description**

Completed by:

Disc Wheel 8

Axle Serial No. 799

	1st	2nd	3rd	Smallest Value	Disc Renewed
Outside Wall Thickness	0.902	0.919	0.915	0.902	Yes _____ No <input checked="" type="checkbox"/>
Inside Wall Thickness	0.965	0.949	0.954	0.949	
Face-to-Face	3.740	3.734	3.736	3.734	

A-END TRUCK SERIAL # 118 B-END TRUCK SERIAL # 107

C-C 106 **Inspect trucks and wheel slide speed sensors.**

SRT-15"

- Inspect truck frames, bolsters and ground straps.
- Inspect truck frame and bolster for cracks that may effect structural integrity. Ensure ground straps are in place and properly secured.
- Inspect bolster anchor assemblies, brackets and hardware. Ensure drag link and bracket and bolster link assembly is not cracked, broken or damaged and is properly secured.
- Inspect air spring assemblies and chevron springs. Inspect the air spring rubber assembly for grease and oil contamination, cuts, tears, and excessive abrasion. Closely inspect the rubber around the girdle hoop. Visually check that the leveling valve lever is in the horizontal position. Use spring height GO/NO-GO gauge, measure spring height. The normal working height of the air spring is 8-7/8 inches. Also check the position of the truck locking bolt where it passes through the truck locking bracket. Nominal clearance is 3/8 in. and minimum clearance is 1/8 in. Correct centering is equal spacing between truck locking bolt and truck locking bracket. If not in proper position, problem may be broken or missing stabilizer bars or leaking air spring assemblies.
- Inspect vertical & lateral dampers and friction snubbers. Inspect dampers for broken, or missing mounting hardware, cracked or broken mounting bracket. Check for oil leakage and the reservoir tube wet with oil. Inspect for damaged or dented casings.
- Inspect laminated traction and side bearer pads. Check pads for proper position and are not damaged or show indications of stress. Check for sharp metal edges in contact with the free rubber surface. Remove burrs carefully using a file. Do not damage the rubber surface. Inspect and replace pads that have cracks or splits that exceed a depth of 3/8 in.
- Inspect pedestal tie bars. Inspect for damage and is properly secured.
- Inspect wheel slide speed sensors, check air gap and cabling. Verify the green wheel slide failure (WSF) indicator light located below the E-7 (No Suggestions) controller at the "A" end of the car is illuminated. Inspect and adjust the wheel slide speed sensors. Check the gap between the magnetic pickup assembly and the split hear. Gap should be 0.025 in ± 0.005 in. Use low pressure air (less than 30 psig) to clean and blow off any excessive buildup of dirt.

C-C 107 **Inspect cabling, conduit, piping and connections.**

SRT-15"


- Inspect under car for indication of a debris strike. Inspect under car wiring and clamps, piping, connections, unions, joints, valves and handles for damage.

RESULTS SHEET – CAR AIR BAG AND FLOOR HEIGHT ADJUSTMENTS

WHEEL #2 WHEEL #4
SPRING #2

WHEEL #6 WHEEL #8
SPRING #4

B-END



SPRING #1
WHEEL #1 WHEEL #3

SPRING #3
WHEEL #5 WHEEL #7

A-END

CHECK ITEM		EXPECTED VALUE	ACTUAL VALUE								
			AXLE 1		AXLE 2		AXLE 3		AXLE 4		
			WH 1	WH 2	WH 3	WH 4	WH 5	WH 6	WH 7	WH 8	
PRE-TRUING MEASUREMENT	SHIMS ADDED	-1/4" TO 1-1/4"	0	0	0	0	0	0	0	0	0
	CLEARANCE BETWEEN BEARING HOUSING & PEDESTAL ARCH (H4)	1-1/2" TO 2-3/4"	2"	2"	2"	2"	2"	2"	2"	2"	2"
POST-TRUING MEASUREMENT	SHIMS ADDED	-1/4" TO 1-1/4"									
	CLEARANCE BETWEEN BEARING HOUSING & PEDESTAL ARCH (H4)	1-1/2" TO 2-3/4"									
AIR BAG (SPRING) HEIGHT (H3)	8-11/16" TO 9-1/16"		SPRING 1		SPRING 2		SPRING 3		SPRING 4		
	GAUGE LOW LIMIT = 8-11/16" GAUGE MID POINT = 8-7/8" GAUGE HIGH LIMIT = 9-1/16"		8 1/4		8 1/16		8 1/16		8 1/16		
PRE-TRUING MEASUREMENT	FLOOR HEIGHT B-END & A-END	50-5/8" TO 51-3/8"	B-END LEFT	B-END RIGHT	A-END LEFT	A-END RIGHT					
			51"	50 3/4	50 3/4	50 3/4					
POST-TRUING MEASUREMENT	FLOOR HEIGHT B-END & A-END	50-5/8" TO 51-3/8"	B-END LEFT	B-END RIGHT	A-END LEFT	A-END RIGHT					






LEVELING RODS TORQUE SEALED

PERFORMED BY [REDACTED]

DATE

12-31-14

<u>Task ID</u>	<u>Description</u>
	<u>Car Exterior</u>
C-C 108 SRT-5"	Inspect sides of car, end caps, and diaphragms. Inspect body panels for damage creating jagged or sharp edges. Check for and remove any signs of graffiti.
C-C 109 SRT-5"	Inspect side doors, steps and inspection panels. Inspect doors and area around doors for damage, jagged or sharp edges. Ensure door windows are not cracked or broken and window gaskets are not torn cracked and are in place. Inspect side door steps and yellow anti-slip edge material. Exterior side steps must be free of tripping hazards. Check for damage resulting from vandalism or from a debris strike. Step grates must not be cracked, broken, bent and properly secured. Ensure the yellow anti-slip material is applied to the outer edge of the step surface, clean and effective. Inspect the truck inspection panels and ensure panels and latches are not damaged, hinge and hinge pin are in place and secured. Inspect condition of cable, hook and bracket at each panel.
C-C 110 SRT-5"	Inspect all windows and condition of gaskets. Ensure glass is not cracked or broken, window gaskets are in place and not torn. Emergency window filler gaskets split is at the bottom of the window with a 1 inch separation.
C-C 111 SRT-5"	Inspect condition of all exterior decals. Inspect condition of car number, authority & locator decals. Ensure that all number signs, authority logos, and car locator decals are in place, legible, and not discolored or faded. Inspect condition of wheelchair, no smoking and bike decals. Ensure that each decal is in its proper place, legible, and not discolored or faded. Inspect emergency window access & removal decals. Each emergency access window must have a fireman locator decal and an emergency window removal decal that provides instructions for operation or removal. Decals must be retro-reflective material. Decals must be in place, legible, and not faded or peeling. Check emergency door locator & instruction decals. Emergency access door locator and instruction decals must be displayed adjacent to each emergency door pull box at doors 3, 5, 4 and 6. Decals must be retro-reflective material. Decals must in place, legible and not faded or peeling.
C-C 112 SRT-5"	Inspect sill steps , horizontal and vertical handholds. Ensure all sill steps are secure with no indication of loose bolts or fasteners. Inspect for shiny areas or rust around fastener heads indicating the fastener may be loose. With bolt heads and nuts welded, check for broken welds. Ensure steps are not bent, cracked or broken. Outside edge of the tread shall not be more than 2" inside the side of the car. Check that the PVC roof drain is in place, and not broken or damaged. Ensure all handholds are secure with a minimum 2 inches of clearance, not cracked or broken. Check for obstructions preventing the use of the handhold.
C-C 113 SRT-5"	Inspect condition of indicator lights and door open assemblies. Ensure indicator lights and housing is not broken or damaged and operate as intended. Repair or replace indicator lights found defective. Check hardware for proper securement and for sharp edges.
C-C 114 SRT-5"	Inspect condition of evaporator, condenser & speaker grilles. Inspect grilles on each side of car. Ensure each is properly secured and not damaged. Check that grilles are clean and not obstructed.



Task ID Description

Completed by:

Cab Car Exterior

- CC-C 115 Inspect headlight, auxiliary, number & marker light housings.
SRT-5" Inspect for damage and housings are properly secured.
- CC-C 116 Inspect end door, window, barrier bar and curtain.
SRT-5"
- CC-C 117 Visually inspect upper horn (if equipped), lower horn and bell.
SRT-5" Check lower horn and bell for indications of damage caused by a debris strike.
- CC-C 118 Inspect axle generator and cabling. Inspect pilot height.
SRT-5" Record front pilot height measurements:

NA

NA

NA

NA

Front Pilot/Plow Height Left Right
 NA NA 3" Min. 6" Max.

Car Interior

- C-C 119 Inspect condition and securement of seats and tables.
SRT-60" Ensure hardware securing seat shells to frame and hardware securing frame to wall mounted frames is not loose. Ensure arm rests and seat dividers are secured.

Check for sharp edges on tables. Replace table top if chipped or cracked. Ensure hardware securing table pedestal at top table and floor mount is tight.

[Redacted]

- C-C 120 Inspect ADA seats, wheelchair restraints and ramp.
SRT-5" Ensure ADA seats raise and lock in the up position and can be lowered using the release handle. Ensure folding legs are not missing, bent, broken or inoperative.

Ensure wheel chair ramp is not damaged or broken. Check hinges for damage. Tie down straps should be tight and bottom strap secured properly.

[Redacted]

- C-C 121 Inspect condition of floors, steps, handrails and handholds.
SRT-20" Inspect for conditions that may cause a tripping hazard. Check that "T" caps are in place and flush with carpet or tile and do not create a tripping hazard. Ensure low location exit path strips are secured to the sub floor and do not create a tripping hazard.

Ensure nosing on all steps is not loose and matches the level of the flooring material and is of a contrasting color. Repair or replace loose carpeting, step riser material, and nosing if tripping hazard is found. Handrails must be secure and provide at least 2 inches of usable clearance.

Ensure all handholds and handrails are properly secured checking for loose bolts or fasteners with at least 2 inches of clearance. Ensure handholds are not bent with no obstruction preventing its use.

[Redacted]

- C-C 122 Inspect condition of ceiling and wall panels and trim.
SRT-20" Ensure panels and molding is not cracked or broken and molding is in proper position.
Ensure cove panels are not cracked, broken, or damaged.

[Redacted]

- C-C 123 Inspect interior lighting and test emergency lighting.
SRT-5" Ensure all lighting throughout car is working properly. Replace burned out lamps and ballast as needed. Ensure cove light lens and caps are not broken or cracked.
Ensure emergency lighting operates as intended:
 - a) Ensure the battery switch is in the ON position.
 - b) Ensure all circuit breakers for interior lights are up or closed.
 - c) Open or turn off the "FWD MAIN SERVICES" and "REAR MAIN SERVICES" circuit breakers.
 - d) Check upper level, mid-level and lower level to ensure emergency lighting operates as intended.
 - e) Turn "FWD and REAR" Main Services circuit breakers on.

Task ID **Description**
C-C 124 **Inspect condition of windows and gaskets.**
SRT-10" Check for windows that are cracked or broken. Inspect for graffiti etched in window or gasket. Check for gaskets that appear to sag, indicated inner portion of gasket is cut.

C-C 125 **Measure & record pull force of emergency exit windows.**
SRT-120" Randomly select eight (8) interior emergency exit windows and perform a manual pull test using a pull force indicator to measure the force required to remove windows. Check form SMP 200 completed at time of last maintenance to avoid testing the same windows.

Maximum Pull Forces:

Cars Numbered 101-182, Cab Cars 601-637: 60 lbs. Maximum allowable pull force when measured at an angle parallel to the floor.

Cars Numbered 183-210: 30 lbs. Maximum allowable pull force when measured at a 30 to 60 degree angle to the floor.

Important Note: If any defective condition is noted on any of the windows in the car or if the pull force limit is exceeded on any of the four (4) windows tested, **ALL** of the emergency windows must be tested.

Form SMP 200, Emergency Window Tests, must be completed and retained for two (2) years in the car's maintenance file.

C-C 126 **Inspect and check operation of all doors.**

SRT-15" **Inspect all door motors and associated hardware.**
Tighten any leaking hose connections. When any internal leakage is found, replace the door motor assembly. Check the electro pneumatic valves for air leaks. If leaks are found, replace the valve.
Inspect & test door operation from both door control stations:
Check both door control stations for loose hardware, check all terminal connections for tightness and continuity, the slide panel completely clears door buttons, and the PA/INT indicator lights function. Clean away any dust or lint using low pressure dry compressed air. Clean and apply DriSlide, a molybdenum disulfide lubricant to the side door ball retainers. Test all door functions from each door control station including the door enable feature and the crew door. Check that the door control system energizes the doors by observing that each door open and close in a smooth, complete way checking:

- a) the doors open and close simultaneously at each door entrance.
- b) with the doors closed, check that the door rubber seals fit properly and that no gaps exist.
- c) if the door drags, check by a problem with the door tracking.
- d) if a door does not open or close fully, there is a problem with the door linkage.


Check for worn or frayed bristles on brush seals. And worn or torn rubber seals.

Door operator adjustment screw are located on the large cylinder of the door motor operator. Adjust screws include:

Door Cushioning Adjustment: Use for adjusting the door's cushioning to prevent the door from slamming open and recoiling. Rotate the screw clockwise for more cushioning, or counterclockwise for less cushioning. Make all adjustments in small increments (1/4 turn or less).

Door Opening Speed Adjustment: Door opening speed should be 1.6 to 2.0 seconds. Rotate the screw clockwise to increase opening speed or counterclockwise to decrease opening speed. Make adjustments in small increments (1/4 turn or less).

Door Closing Speed Adjustment: Door closing speed should be 2.0 to 2.6 seconds. Rotate the screw clockwise to increase door closing speed or counterclockwise to decrease door closing speed. Make adjustments in small increments (1/4 turn or less).



Task ID **Description**



Check ADA sonalert, door lights and exterior indicator lights.
Sonalert alarm sounds intermittently and starts when door close buttons are energized and should sound for 2 - 3 seconds before doors begin to close. White door lights will also begin to flash when door close buttons are energized and continues until doors are closed.

Inspect and operate end doors.

Adjust end door closer mechanism or use speed adjusting screw as need for correct operation. Closing force of on door panel leading edge should be approximately 5 lbs. Inspect weather stripping for damage. Lubricate the top hung sliding end doors and hinges on cab car end doors using DriSlide.

Inspect and test emergency door pull cable rings.

Ensure that the frangible plastic cover is in serviceable condition and is not cracked or broken. Remove the cover housing, pull the cable ring until the door opens or releases sufficiently to be opened manually. Ensure cable is free moving and not frayed. Replace cover housing and tighten hardware.



C-C 127 **Check condition of interior decals and posters.**
SRT-10"

Inspect emergency exit window decals.


All emergency window exits must be identified with EXIT decals including window removal instructions of photo luminescent material. The decals must be in place, legible, not faded or peeling.

Inspect emergency exit door decals.

Decals must be in place located at emergency door pull locations at doors 3, 5, 4 and 6. Decals must be of photo luminescent material, must be legible, not faded or peeling.

Inspect emergency evacuation, safety & system map posters.

Inspect poster frames for sharp edges. Emergency evacuation poster must be displayed in frame located on lower level on sloped wall "A" end of car. Check for graffiti and not bent or creased.



C-C 128 **Inspect electrical system and check for systems for grounds.**
SRT-20"

Inspect electrical cabinets and lockers and check decals.

Inspect wiring and insulation, check all electrical components for indications of overheating. Check to ensure wires are firmly attached and routed properly. Check circuit breakers ensuring that each spring and latch when closed and circuit breaker does not bind.


Check battery charging. Open the access panel at the "B" end circuit breaker panel. Check the battery status monitor for the following:

- a) Status Normal green lamp is illuminated.
- b) Battery Percent Capacity meter registers a reading above 50.
- c) No red lamps are illuminated.

Ensure "DANGER - High Voltage" decals are in place and legible on hi-voltage cabinet.

Check for low voltage grounds.

Check for high voltage system grounds.



C-C 129 **Self test E-7 wheel slide/system and correct faults if required.**
SRT-5"

C-C 130 **Inspect HVAC, heater strip and air filter grilles.**
SRT-90"

a) Check the oil level in the compressor crankcase sight glass. The level should be approximately 1/2 the sight glass.

b) Check all electrical circuits for continuity and tight connections.






c) Check the following for grounds, using a 500 V Megger, a 1 megaohm or greater is acceptable:

- 1. Compressor motor
- 2. Condenser fan motor
- 3. Evaporator blower/motor

d) Inspect the motors for dirt, friction, vibration, and proper rotation. Vacuum any dirt from the motor.

e) Check the oil and refrigerant levels during steady state operating conditions (275 psig discharge pressure and 70 psig suction pressure).

f) Check the refrigerant lines for leaks using a leak detector.

<u>Task ID</u>	<u>Description</u>	<u>Completed by:</u>
	<p>g) If necessary, repair leak and add refrigerant and oil.</p> <p>h) Monitor the moisture and liquid indicator to determine the system dryness of refrigerant. If a condition other than Safe or Dry is indicated, change the filter-drier assembly.</p> <p>i) Inspect the resilient mounts for set or surface cracks.</p> <p>j) Inspect the surface of the condenser and evaporator coil. Remove any major blockage and clean the surface.</p> <p>k) Inspect the drain pan under the evaporator coil and the drain lines to ensure free water drainage.</p> <p>l) Clean the temperature sensors and thermostats with a soft cloth.</p> <p>m) Lubricate evaporator fan shaft bearings and condenser and evaporator motor bearings with grease. Check alignment tension and condition of fan bells and couplings. If the bell is correctly tensioned, the bell should deflect 1/4 inch at the center of the span if a force of 8 lbs. is applied at that point perpendicular to the belt.</p> <p>n) Test the HVAC system with the heating and air conditioning sequence tester.</p> <p>Inspect heater strip and air filter grilles.</p> <p>Inspect for loose or missing hardware securing the heater grill or air filter grille. Ensure latches securing the air grilles function properly and tightly secures the air grille in place.</p>	
C-C 131 SRT-5"	<p>Inspect windscreens, access doors and bicycle straps.</p> <p>Inspect condition & securement of windscreens:</p> <p>Ensure glass wind screens are not broken or cracked with no sharp edges, and are secure in mountings.</p> <p>Inspect all access panel doors and latches.</p> <p>Ensure all access panel doors, hinges and latches are not broken or damaged. Secure all panel door latches upon completion of inspection.</p> <p>Inspect condition of bicycle rack securement.</p> <p>Check securement of brackets and condition of nylon cord.</p>	
C-C 132 SRT-10"	<p>Check emergency flashlight-tools-first aid kit-fire extinguishers.</p> <p>Emergency flashlight, tools and first aid kit:</p> <p>Inspect condition of frangible glass, gasket and pull ring if equipped. Check that emergency equipment, including emergency flashlight, saw, sledge hammer, pry bar, axe, and a maul is in place and in serviceable condition. Observe LED on flashlight is flashing indicating batteries are in serviceable condition. Inspect condition of bracket and that seal is in tact. Ensure first aid kit is in place and sealed (shrink wrapped). If not sealed, replace first aid kit.</p> <p>Check all fire extinguishers:</p> <p>Remove fire extinguisher and ensure seal is not missing or broken. Check that gauge is not damaged and needle is in the green zone indicating proper pressure. Check for defects in the hose, nozzle, corrosion to canister and other visible defects. Ensure inspection tag is in date (1 year) and will remain in date before next maintenance due date (92 days). Clean compartment, inspect housing and frangible glass. Place fire extinguisher in holder, and is secure.</p>	
C-C 133 SRT-10"	<p>Inspect and test destination sign controller and signs.</p> <p>Check operation of destination sign controller and signs ensuring it is operating as intended.</p>	
C-C 134 SRT-5"	<p>Check operation and dB level of PA and intercom.</p>	
C-C 135 SRT-5"	<p>Check drinking water fountain and trash receptacles.</p> <p>Check operation of water fountain and inspect for broken or damaged parts. Water pressure should be approx. 14 lbs.</p> <p>Inspect trash receptacles for damage, being bent, cracked, or having sharp corners or edges.</p>	

Task ID **Description**

C-C 136 **Inspect diaphragms, vestibule curtains and walkway plates.**

SRT-10" Diaphragms: Inspect aluminum mounting plate, sponge return spring, stainless steel fasteners and the graphite phenol resin wear plate. Check tightness of hardware, holes or tears in rubber parts, cracks or broken wear plates, bent or cracked face plate or mounting plate.

 Vestibule Curtains: Inspect upper and lower roller brackets for damage, curtains for holes or tears, and curtains recoil properly and are spring loaded.

 Check footing condition in walkway areas including the effectiveness of yellow anti slip surface. Replace walkway plugs if missing.

Completed by: [Redacted]

C-C 137 **Check emergency brake cable - check & lubricate handbrake.**

SRT-10" Check emergency brake valve cable pull and decals.

 Ensure handles are in place, not obstructed from use and decals are in place and legible.

 Inspect, test and lubricate handbrake:

 Inspect handbrake rigging for wear and free movement. Lubricate lever fulcrum pins. Adjust cable slack, if required, and ensure slack adjuster is secure.

[Redacted]

Cab Car Interior

CC-C 138 **Check instrument panel-cab-indicator lights-all exterior lights.**

SRT-5" Inspect all gauge and panel lights including speed indicator and gauge dimmer switch. Operate push to test feature to verify lamps are working properly.

 Ensure proper operation of all exterior lights.

 1) Front Headlight (all positions).

 2) Auxiliary lights (steady state and flashing).

 3) Marker lights.

[Redacted] NOT A CAB CAR 12/1/7

CC-C 139 **Inspect & test air gauges. Perform brake pipe leakage test.**

SRT-10" Equalizing and brake pipe pressure within 3 lbs.

 Ensure equalizing reservoir needle and brake pipe needle are within 3 lbs. of each other. Increase and decrease equalizing reservoir pressure and note brake pipe pressure responds.

 Test air brake gauges.

 Verify accuracy of each needle (4) using a CO2 tester at 100 lbs. of pressure.

 Perform brake pipe leakage test.

 Brake pipe leakage must not exceed 3 lbs. per minute.

N/A

CC-C 140 **Test air brake-safety controls-warning devices-controller.**

SRT-10" Check operation of 26B automatic brake valve it functions as intended in all positions. Test graduated release feature, TMS and emergency.

 Check controller for proper operation:

 Ensure controller and reverser interlock as intended. Check electrical cannon plug under desk top to ensure connection is tight.

N/A

CC-C 141 **Check ATS-speed recorder-inspect/download event recorder.**

SRT-30" Verify ATS receiver is properly secured and the washboards are aligned.

 Perform a slap test. Perform ATS test and complete form SMP 8.

 Inspect, download, reset time & seal event recorder.

N/A

<u>Task ID</u>	<u>Description</u>	<u>Completed by:</u>
C-C 150 SRT-5"	<p>Inspect condition of floor, handholds, panels and molding.</p> <p>Inspect floor for tripping hazards, and check wall panels and molding for being cracked or broken.</p> <p>Ensure handholds are properly secured and provide 2 inches of usable clearance.</p> <p>Inspect access panel and compartment type doors.</p>	[Redacted]
C-C 151 SRT-5"	<p>Inspect ceiling, plumbing compartment/light and exhaust fan.</p> <p>Inspect exhaust fan & components in plumbing compartment.</p> <p>Inspect plumbing compartment for obvious fluid leaks, check light.</p>	[Redacted]
C-C 152 SRT-5"	<p>Check operation of toilet, sink and inspect mirrors.</p> <p>Inspect sink vanity mirror and wall mounted mirror.</p> <p>Ensure mirrors are not cracked or broken and is properly secured.</p> <p>Check toilet flush timing cycle, check for proper metering of water and biocide.</p> <p>Ensure adequate water seal is maintained in bowl. Check water pressure at sink, (14 psi) and ensure water spring loaded faucet plunger operates as intended and water does not drip.</p>	[Redacted]
C-C 153 SRT-10"	<p>Renew coalescent - particulate and water cooler filters.</p> <p>Remove and clean threaded polycarbonate bowl and renew coalescent and particulate filter elements.</p> <p>Close valve to isolate water cooler from supply tank. Depress valve until water flow ceases. Disassemble threaded body of filter shell and replace cartridge.</p>	[Redacted]

Interior Cleaning

C-CL 101	<p>Remove trash (newspapers, cups). Inspect and remove graffiti.</p>	[Redacted]
C-CL 102	<p>Wash ceilings, walls, bulkheads, windscreens & kickboards.</p> <p>Wash wind screens and kickboards under seats.</p> <p>Do not leave cleaning streaks on wall panels.</p>	[Redacted]
C-CL 103	<p>Clean windows, glass partitions, handrails and handholds.</p> <p>Clean all side and door windows. Clean glass partitions on lower and mid-levels.</p> <p>Clean handrails, stanchions, and handholds. Clean stainless steel door control station covers. Wipe off excess cleaning material.</p>	[Redacted]
C-CL 104	<p>Empty trash. Clean interior-exterior of trash receptacles.</p> <p>Replace plastic trash bags. Ensure slide-out trash receptacles are applied properly.</p>	[Redacted]
C-CL 105	<p>Clean interior and exterior of cove light fixtures.</p>	[Redacted]
C-CL 106	<p>Remove and clean return air grilles & air conditioning vents.</p>	[Redacted]
C-CL 107	<p>Wipe down heater guards and heater boxes.</p>	[Redacted]
C-CL 108	<p>Vacuum seat backs/bottoms-clean headrests-Replace if needed.</p>	[Redacted]
C-CL 109	<p>Clean seat shells, dividers and armrests. Clean-sanitize tables.</p>	[Redacted]
C-CL 110	<p>Clean and disinfect water fountain including drain sink.</p>	[Redacted]
C-CL 111	<p>Clean side doors, windows, and door tracks.</p> <p>Completely clean dirt and debris in all door track. Clean the guide slot of the door threshold. Remove any debris in the door pockets. Ensure drain holes are not plugged.</p>	[Redacted]
C-CL 112	<p>Clean diaphragms, vestibule curtains and walkway plates.</p>	[Redacted]
C-CL 113	<p>Sweep and mop tile floors and steps. Strip & mop floor.</p> <p>Sweep and mop all tile floors including restroom and steps.</p> <p>Strip tile floors, reapply sealant if required and wax floors.</p>	[Redacted]

Task ID Description
 C-CL 114 Vacuum and shampoo all carpeted areas.
 SRT-480" total C-CL 101 - 114

Completed by:
 [Redacted Signature]

Cab Car Interior Cleaning

CC-CL 115 Clean console, side and upper switch and indicator panels.
 CC-CL 116 Clean ceiling and wall panels.
 CC-CL 117 Clean seat, window(s), wall panels & ceiling. Sweep & mop floor.
 Clean crew locker walls and ceiling.
 Sweep and mop crew locker floor.
 SRT-15" total C-CL 115 - 114

NOT
 A CAB CAR
 11/7
 NA
 NA
 NA

Car Exterior

C-CL 118 Wash door pockets, car end caps, and diaphragms.
 SRT-30"
 C-CL 119 Clean side door step platforms and yellow anti slip surface.
 SRT-30"
 C-CL 120 Clean cab car window(s).
 SRT-10"

[Redacted Signature]
 NA
 NA

Review & resolve all outstanding defects.

Review SMP 129, SMP 100 and outstanding defect reports. All defects recorded and those found during inspection must be corrected before car or cab car is released for service.

NOTE: All defects must be corrected before releasing vehicle for service.

Supervisor Reviewing Work Order:

[Redacted Signature]
 Supervisor

Work Order Finished:

1/5/15
 Date

Manager Reviewing Work Order:

[Redacted Signature]

Work Order Closed:

1/7/15
 Date

Car: 211

Date: 1/5/15

Employee Signature: 

A - End Truck: 118

B - End Truck: 107

Axle 1 Serial #: A 167

Axle 2 Serial #: LA 125

Axle 3 Serial #: SQ 71

Axle 4 Serial #: 799

Wheel # 1: 100947

Wheel # 2: 100995

Wheel # 3: 101011

Wheel # 4: 100992

Wheel # 5: 100999

Wheel # 6: 101010

Wheel # 7: 100938

Wheel # 8: 101014


EQUIPMENT NO. SCAX 211

BEFORE TRUING WHEEL MEASUREMENT

AFTER TRUING WHEEL MEASUREMENTS

WHEEL POSITION		DEFECT	BACK TO BACK	FLANGE THICKNESS	FLANGE HEIGHT	RIM THICKNESS
<input checked="" type="checkbox"/> CAR	<input type="checkbox"/> LOCO					
A - END						
8	R1	RP		0	18	42
7	L1	RP		0	18	42
6	R2	RP		0	18	42
5	L2	RP		0	18	42
4	R3	RP		0	18	42
3	L3	RP		0	18	42
2	R4	FS		0	18	42
1	L4	FS		0	18	42

FLANGE THICKNESS	FLANGE HEIGHT	RIM THICKNESS	OPERATOR COMMENTS
0	17	40	
0	17	40	
0	17	40	
0	17	40	
0	17	40	
0	17	40	
0	17	40	
0	17	40	
0	17	40	



SERVICE LIMITS

BACK TO BACK	53" - 53 3/8"
FLANGE THICKNESS	"0" + 1 or "0" - 0 ON STEEL WHEEL GAGE
RIM THICKNESS	1 1/8" MINIMUM
TAPE SIZE	BOTH WHEELS <= 1 TAPE DIFFERENCE
RUN OUT	< .020"

D E F E C T S	FS	FLAT SPOTS
	BUT	BUILT-UP TREAD
	ST	SHELLING
	HF	HIGH FLANGE
	HC	THERMO CRACKS
	TF	THIN FLANGE
	WT	TREAD WORN HOLLOW
RP/TRUE	REPROFILE/TRUE TO MATCH	

PERFORM DAILY MAINTENANCE YES NO

INDEX INSERTS/CHECK RUN OUT/TAPE YES NO

SINGLE CAR AIR TEST PER CFR 238.311 YES NO

Additional Operator Comments

MACHINE OPERATOR/ ID #: 1863

SUPERVISOR/ ID#: 166464

DATE: 1-06-15

