



**CEN13LA359**

**Jonesboro, Arkansas**

**June 19, 2013**

**1620 CDT**

**Bell Helicopter 206 L-4; N467AE**

**NTSB ENGINE EXAMINATION**

**Examination Date: July 9, 2013**

**PARTICIPANTS IN THE EXAMINATION**

**Shawn Etcher  
Air Safety Investigator  
National Transportation Safety Board  
Ashburn, VA 22611**

**Mark Stuntzner  
Acting Technical Advisor to TSB -  
Canada  
Bell Helicopter  
Dallas, TX**

**Jon-Adam Michael  
Air Safety Investigator  
Rolls-Royce  
Indianapolis, IN**

**Casey Lehman  
Air Safety Investigator  
Rolls-Royce  
Indianapolis, IN**

## **HISTORY OF FLIGHT**

On June 19, 2013, at 1620 central daylight time, N467AE, a Bell 206L-4 helicopter, sustained substantial damage when it made a forced landing after a partial loss of engine power while on final approach to a helipad at the Jonesboro Municipal Airport (JBR), Jonesboro, Arkansas. The commercial pilot, flight nurse, and the paramedic were not injured. The helicopter was registered to a private entity and operated by Air Evac EMS, Incorporated, O'Fallon, Missouri. Visual meteorological conditions prevailed and a company visual flight rules flight plan was filed for the repositioning flight conducted under Title 14 Code of Federal Regulations Part 91. The flight originated from the Southeast Missouri Hospital in Cape Girardeau, Missouri, approximately 1534.

The pilot reported that the helicopter was approximately 80-100 feet above the ground at an airspeed of 40 knots when the engine lost power. He said the power loss was similar to the engine rolling back to flight idle. The pilot said he lowered the collective to conserve rotor RPM, so there would be enough engine power for a "sliding landing." The helicopter touched down at the edge of tall grass/dirt and bounced slightly before it came to rest upright on its skids. The helicopter's skids sustained damage and the tail boom was displaced downward so the stinger was resting on the ground.

According to operator, the helicopter and engine had accrued a total of 154.3 hours since new

## **ENGINE INFORMATION**

Engine Manufacturer: Rolls-Royce  
Engine Model Number: 250-C30P  
Engine Serial Number: CAE896154

## **INITIAL EXAMINATION AS RECEIVED**

The engine was shipped from the operator's facility in West Plains, Missouri to Rolls-Royce facilities in Indianapolis, Indiana via crate and bonded shipment. Upon receipt the engine was immediately logged and placed in bonded/secure storage and was not opened. On July 9, 2013 at 0735 EDT, the crate was viewed by the NTSB and the above listed personnel as unopened; it was photographed and opened for examination. The sealed tags were numbered 922558 and 922591. No representative from the operator was present at the time of the examination. The examination revealed that the freewheeling unit had been removed and was not contained within the shipping crate.



Photo 1: Engine Shipping Crate as Received




Photo 2: Seal Tag No. 922591



Photo 3: Engine Shipping Crate as Received



Photo 4: Seal Tag No. 922558

## **DETAILED EXAMINATION**

### **Engine Overall**

The engine was mounted on an engine test stand and the Serial Numbers were noted in the table below. Filter air was applied to the Pc filter at 50 psi and "SNOOP" leak detecting liquid was applied to all B-nuts and no leaks were detected. Examination did not reveal any abnormalities or malfunctions that could preclude an engine operation in the test cell. The engine was transported to Rolls-Royce Test Cell No. 147 and was mounted for the engine run.



Photo 5: Engine after Shipping Case Removal




Photo 6: Rear Accessory Drive





Photo 7: Fourth Stage Turbine Blades as Viewed in Engine on Engine Stand




Photo 8: Engine Information

| Component       | Serial Number | Part Number | TSO (hrs) | Total Time (hrs) |
|-----------------|---------------|-------------|-----------|------------------|
| Engine 250-C30P | CAE 896154    | 23062065    | 154.3     | 154.3            |
| Gearbox         | CAG 96163     | 23035178    | 154.3     | 154.3            |
| Compressor      | CAC 92402     | 23051643    | 154.3     | 154.3            |
| Turbine         | CAT 98789     | 23035128    | 154.3     | 154.3            |
| FCU             | HR60584       | 23087146    | 154.3     | 154.3            |
| Fuel Pump       | JG10AKW0410   | 23074706    | 154.3     | 154.3            |
| Fuel Nozzle     | VN1BRR1657    | 23077067    | 154.3     | 154.3            |
| Bleed Valve     | FF372338      | 23073353    | 154.3     | 154.3            |
| Governor        | HR49739       | 23086751    | 154.3     | 154.3            |

## ENGINE RUN

The engine was mounted in Rolls-Royce test stand No. 147 and attached with test stand fuel lines. The engine run was accomplished per the Rolls-Royce 250-C30 series overhaul manual. The engine test cell had a recorded temperature of 81°F, the engine was started and operated at various power settings; however, when torque was at 95% the maximum fuel flow was recorded at 376 pounds per hour and was unable to be achieved maximum fuel flow, and the gearbox output speed began to decrease and did not achieve the output speed of 6016 rpm. The engine power was reduced to idle and then shut down to facilitate adjustment of the "max flow stop" on the fuel controller. The engine was restarted and again accelerated through various required power settings up to and including maximum takeoff power. The Bleed valve was verified closed within the normal range and no vibration exceedances were noted. The anti-ice was utilized and operated within a normal range. The governor check was accomplished and was normal in operation. Then engine was operated at about 78% torque and then decreased to flight idle (which is 100% power turbine speed, on the ground, flat pitch on the main rotor blades) then accelerated to takeoff power with no hesitation or abnormalities noted; this procedure was accomplished twice with similar results. The Engine was stabilized at ground idle for 1 minute then accelerated to the flight idle setting. The engine accelerated to takeoff power in 0.48 seconds. The test data correlates to 678.6 shaft horsepower, or 5.8% above rated power, at takeoff. For further test information reference Appendix A and Appendix B of this report.



Photo 9: Engine Mounted in Test Stand



Photo 10: Max Flow Stop

### **SUMMARY**

The engine examination and run did not reveal any abnormalities that would have precluded normal operation including the capability of producing power during the accident sequence. Although the initial test run indicated that the engine was not producing maximum gearbox output speed, Rolls-Royce indicated that the maximum fuel flow is set in the factory at the maximum setting and the operator is required to set the fuel flow for the specific aircraft type. In the case of the Bell 206 L-4 the initial setting appeared to be correct for the aircraft type. Therefore it is probable that the engine, at the time of the accident, did not rollback or operate at a sub-idle setting.

### **FUTURE ACTIVITIES**

None are planned at this time for this engine. The engine will be returned to the operator in West Plains, Missouri and kept with the accident helicopter in preparation for the release of the wreckage by the National Transportation Safety Board IIC.



Photo 11: Engine Crated for Shipment to Operator

## **Appendix Table of Contents**

**Appendix A - Engine Test Log photographed copy**

**Appendix B - Engine Test log scanned copy**

# Appendix A

## Engine Test Log - Photograph Copy

The image shows a photograph of a Rolls-Royce Engine Test Log for a 250 Series engine. The log is a large, multi-column grid with various sections for recording test data. The top right corner features the Rolls-Royce logo and the text "ENGINE TEST LOG 250 SERIES". The grid contains numerous rows of data points, with some handwritten entries. The bottom of the log has several summary fields for test parameters and results.

Photo 12: Engine Test Log Raw Test Data Numbers

## **Appendix B**

### **Engine Test Log Copy (2 Pages)**



|                   |       |  |  |  |  |                       |  |  |  |  |  |  |
|-------------------|-------|--|--|--|--|-----------------------|--|--|--|--|--|--|
| TIME              | 10:30 |  |  |  |  | Rolls-Royce Allison   |  |  |  |  |  |  |
| TRUE BAR.         | 29.33 |  |  |  |  | P.O. Box 420          |  |  |  |  |  |  |
| OUTSIDE TEMP.     | 80°   |  |  |  |  | Indianapolis, Indiana |  |  |  |  |  |  |
| RELATIVE HUMIDITY |       |  |  |  |  | 46206-0420 USA        |  |  |  |  |  |  |

| GENERAL                  | DATA REQUIRED             | UNITS           | 1     | 2     | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12    |
|--------------------------|---------------------------|-----------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|                          |                           | TIME MIL. CLOCK | hh:mm | 10:40 | 11:04 | 11:08 | 11:12 | 11:20 | 11:25 | 11:30 | 11:44 | 11:50 | 11:59 | 12:08 |
|                          | POWER SETTING             |                 | 3768  | 5768  | VIB   | Noise | A/E   | GOV   | 78%   | DECEL | Accel | DECEL | Accel | Power |
|                          | GAS PRODUCER SPEED (N1)   | rpm             | 32527 | 32505 | 51417 | Start | 50053 | DEOP  | of    | 35K   | 78%   | 35K   | 78%   |       |
|                          | DYNE SPEED                | rpm             | 4324  | 4308  | 6009  | F.I   | 6012  | CK.   | T10   | F.I   | T10   | F.P.  | 49/98 |       |
|                          |                           |                 |       |       |       | 32704 |       | 36209 |       | 34126 | 49277 | 34311 | 6070  |       |
|                          |                           |                 |       |       |       | 5475  |       | 6426  |       | 5964  | 6024  | 5970  |       |       |
| HORSEPOWER               | DYN. FORCEMETER           | ft/lb           | 37.4  | 32.5  | 590.0 | 7.8   | 517.8 | 11.6  | (460) | 7.0   | 460.5 | 4.6   | 460   |       |
|                          | DYN. FORCEMETER           | hp              |       |       |       |       |       |       |       |       |       |       |       |       |
|                          | ENGINE TORQUEMETER        | psig            | 5.0   | 5.2   | 95.5  | 1.0   | 84.0  | 2.5   |       | 1.5   | 1090  | 1.5   | 1086  |       |
|                          | CORR. SHAFT HORSEPOWER    | hp              |       |       |       |       |       |       |       |       | 7.5   |       | 7.5   |       |
| FUEL                     | FUEL INLET PRESSURE       | psig            |       |       |       |       |       |       | 15    |       |       |       |       |       |
|                          | OBSERVED FUEL FLOW        | lb/hr           | 103   | 101   | 380   | 98    | 341   | 114   |       | 103   | 313   | 104   | 311   |       |
|                          | FUEL INLET TEMP.          | °F              |       |       |       |       | 346   | 84    |       |       |       |       |       |       |
|                          | CORR. FUEL FLOW           | lb/hr           |       |       |       |       |       |       |       |       |       |       |       |       |
| COMPRESSOR               | ANTI-ICE LINE TEMPERATURE | °F              |       |       |       |       | 104   | 102   |       |       |       |       |       |       |
|                          | AVG. COMP. INLET PRESSURE | in HgA          |       |       |       |       | 154   | 122.5 |       |       |       |       |       |       |
|                          | EXH. STATIC PRESSURE      | in HgA          |       |       |       |       |       | 29.11 |       |       |       |       |       |       |
|                          | AVG. COMP. INLET TEMP.    | °F              | 82    | 82    | 83    | 83    | 83    | 84    |       | 84    | 84    | 85    | 85    |       |
|                          | TEST CELL REF. TEMP.      | °F              |       |       |       |       |       | 85    |       |       |       |       |       |       |
|                          | VENTURI Δ P               | psid            |       |       |       |       |       |       |       |       |       |       |       |       |
|                          | VENTURI ATM. PRESS.       | psia            |       |       |       |       |       |       |       |       |       |       |       |       |
|                          | VENTURI REF. TEMP.        | °F              |       |       |       |       |       |       |       |       |       |       |       |       |
|                          | PLENUM Δ P                | in H2O          |       |       |       |       |       |       |       |       |       |       |       |       |
|                          | COMP. DISCHARGE TEMP.     | °F              |       |       |       |       |       |       | 370   |       |       |       |       |       |
| COMP. DISCHARGE PRESSURE | in HgA                    | 80              | 82    | 248   | 79    | 234   | 97    |       | 87    | 210   | 88    | 220   |       |       |
| GEARBOX CASE PRESSURE    | in H2O                    | .6              | .6    | .6    | .7    | .5    | 1.1   |       | 1.0   | 0     | 1.0   | 0     |       |       |
| COMP. SEAL VENT PRESSURE | in Hg                     | 2.6             | 1.4   | 10.0  | 1.0   | 10.5  | 1.6   |       | 1.1   | 9.0   | 1.2   | 9.6   |       |       |
| TURB.                    | IND. MGT                  | °F              | 1333  | 1388  | 1409  | 895   | 1337  | 916   |       | 897   | 1272  | 902   | 1270  |       |
|                          | CORR. MGT                 | °F              | 919   | 898   |       |       | 1365  |       |       |       |       |       |       |       |
| OIL                      | MAIN OIL PRESSURE         | psig            | 118   | 118   | 122   | 116   | 120   | 116   |       | 118   | 120   | 118   | 120   |       |
|                          | SCAVENGE OIL PRESSURE     | psig            |       |       |       |       |       | 20    |       |       |       |       |       |       |
|                          | OIL INLET PRESSURE        | psig            |       |       |       |       |       | 1.5   |       |       |       |       |       |       |
|                          | SCAVENGE OIL TEMPERATURE  | °F              |       |       |       |       |       | 231   |       |       |       |       |       |       |
|                          | OIL INLET TEMPERATURE     | °F              | 126   | 175   | 188   | 190   | 190   | 192   |       | 198   | 191   | 197   | 198   |       |
|                          | OIL FLOW TIME (5 lb)      | min             |       |       |       |       |       |       |       |       |       |       |       |       |
| OIL FLOW                 | lb/min                    |                 |       |       |       |       |       |       |       |       |       |       |       |       |
| VIBRA.                   | DYNE VIBRATION            | in/sec          | .11   | .44   | .88   | .33   | .79   | .69   |       | .69   | .74   | .75   | .24   |       |
|                          | GEARBOX VIBRATION         | in/sec          | .07   | .08   | .13   | .07   | .11   | .09   |       | .08   | .11   | .08   | .11   |       |
|                          | TURBINE VIBRATION         | in/sec          | .10   | .09   | .17   | .08   | .13   | .10   |       | .11   | .11   | .11   | .11   |       |
|                          | COMPRESSOR VIBRATION      | in/sec          | .08   | .10   | .15   | .08   | .16   | .16   |       | .15   | .17   | .14   | .17   |       |
|                          | START ACCEL & DECEL TIME  | min             | .555  | .478  |       |       |       |       |       | .066  | .048  | .056  | .048  |       |
|                          | START NUMBER              |                 | 1     | 2     |       |       |       |       |       |       |       |       |       |       |
|                          | DOWN                      |                 | 11:50 |       |       |       |       |       |       |       |       |       |       |       |
|                          |                           |                 |       |       |       |       |       |       |       |       |       |       |       |       |

| OIL CONSUMPTION |       |      |         | FUEL DRAINAGE |                   |        |                    |
|-----------------|-------|------|---------|---------------|-------------------|--------|--------------------|
| OIL AT:         | TOTAL | TIME | ELAPSED | TOTAL OIL     | COMB. CHAM        | cc/min | FUEL PUMP DRAIN    |
| START           |       |      | TIME    | CONS lb/hr    | EXH. COL. DRAIN   | cc/min | BURNER DRAIN VALVE |
| FINISH          |       |      |         |               | FIRE SHIELD DRAIN | cc/min | TOTAL FUEL GAL.    |

|                    |                                       |                        |                           |                        |
|--------------------|---------------------------------------|------------------------|---------------------------|------------------------|
| <b>Rolls-Royce</b> | <b>ENGINE TEST LOG<br/>250 SERIES</b> | TEST No. <u>106759</u> | ENGINE S/N <u>896154</u>  | MODEL <u>C90P (H)</u>  |
|                    |                                       |                        | TYPE TEST <u>Memo</u>     | DATE <u>7-9-13</u>     |
|                    |                                       |                        | LOG SHEET No. <u>1</u>    | STAND <u>147</u>       |
|                    |                                       |                        | P.T.S. No. <u>B27 RFD</u> | OIL TYPE: <u>23699</u> |

| 3     | 14    | 15    | 16    | 17    | 18 | 19    | 20 | 21 | 22 | 23 | 24 | 25 |
|-------|-------|-------|-------|-------|----|-------|----|----|----|----|----|----|
| 12:18 | 12:24 | 12:30 | 12:36 | 12:42 | :  | 12:46 | :  | :  | :  | :  | :  | :  |
| 2     | 3     | 4     | 5     | 6     |    | G.I.  |    |    |    |    |    |    |
| 47348 | 48774 | 49629 | 50478 | 51563 |    | 32667 |    |    |    |    |    |    |
| 6015  | 6008  | 6021  | 6013  | 6011  |    | 4326  |    |    |    |    |    |    |
| 359.0 | 430.4 | 473.0 | 516.8 | 585.4 |    | 30.5  |    |    |    |    |    |    |
| 58.0  | 69.5  | 76.0  | 83.5  | 95.0  |    | 5.0   |    |    |    |    |    |    |
| 15    | 15    | 15    | 15    | 15    |    |       |    |    |    |    |    |    |
| 262   | 296   | 318   | 342   | 376   |    | 99    |    |    |    |    |    |    |
| 90    | 90    | 90    | 90    | 90    |    |       |    |    |    |    |    |    |
| 108   | 113   | 116   | 117   | 117   |    |       |    |    |    |    |    |    |
| 29.15 | 29.12 | 29.12 | 29.11 | 29.10 |    |       |    |    |    |    |    |    |
| 29.24 | 29.24 | 29.25 | 29.26 | 29.26 |    |       |    |    |    |    |    |    |
| 85    | 86    | 86    | 86    | 86    |    | 86    |    |    |    |    |    |    |
| 88    | 89    | 89    | 89    | 89    |    |       |    |    |    |    |    |    |
| 575   | 605   | 624   | 641   | 667   |    |       |    |    |    |    |    |    |
| 198   | 215   | 224   | 234   | 248   |    | 80    |    |    |    |    |    |    |
| 7.2   | 8.0   | 8.6   | 9.0   | 9.7   |    | .9    |    |    |    |    |    |    |
| 1173  | 1248  | 1295  | 1337  | 1414  |    | 903   |    |    |    |    |    |    |
| 118   | 120   | 120   | 120   | 120   |    | 116   |    |    |    |    |    |    |
| 25    | 25    | 26    | 26    | 26    |    |       |    |    |    |    |    |    |
| 1.0   | 1.0   | 1.0   | 1.0   | 1.0   |    |       |    |    |    |    |    |    |
| 257   | 261   | 263   | 267   | 270   |    |       |    |    |    |    |    |    |
| 195   | 196   | 196   | 197   | 197   |    | 195   |    |    |    |    |    |    |
| 77    | 90    | 94    | 93    | 96    |    | 38    |    |    |    |    |    |    |
| 12    | 11    | 11    | 11    | 12    |    | .08   |    |    |    |    |    |    |
| .09   | .11   | .11   | .15   | .16   |    | .10   |    |    |    |    |    |    |
| .16   | .16   | .17   | .16   | .15   |    | .09   |    |    |    |    |    |    |
|       |       |       |       |       |    | 12.50 |    |    |    |    |    |    |
|       |       |       |       |       |    | 1.46  |    |    |    |    |    |    |

|                       |                    |                      |
|-----------------------|--------------------|----------------------|
| TYPE FUEL <u>JOTA</u> | LHV <u>18538.5</u> | SP. GR. <u>.8160</u> |
| CUSTOMER MON. N1 N2   |                    |                      |
| COL.                  | N1                 | N2                   |
| IDLE                  |                    |                      |
| CC                    |                    |                      |
| TO                    |                    |                      |

REMARKS: NEED TO ADJUST  
MAX FUEL FLOW.

| MAG. PLUG |      |      |       |        |
|-----------|------|------|-------|--------|
|           | COL. | LOC. | COND. | ACTION |
| 1         |      |      |       |        |
| 2         |      |      |       |        |
| 3         |      |      |       |        |
| 4         |      |      |       |        |

|            |        | SEA LEVEL - STATIC (UNITY RAM) PERFORMANCE |       | SFC: MAX/CORR |          | WFC: MAX/CORR |      |
|------------|--------|--|-------|---------------|----------|---------------|------|
|            |        |  |       | MAX           | CORR     | MAX           | CORR |
| SETTING    | TOT #  | hp   | C/L1A | C/L1B         | MAX C.F. | T/O           |      |
|            |        |  |       |               |          |               |      |
| MIN. ALLOW | % VAR. |  | 540   | 12.6          | 612      | 663           |      |
| SFC        |        |  | .597  | .571          | 9.0      | 5.8           |      |
| MAX. ALLOW | % VAR. |  | .647  | .611          | .564     | .562          |      |
|            |        |  | -7.7  | -6.5          | -5.8     | -5.1          |      |

|                |      |           |                                     |             |  |
|----------------|------|-----------|-------------------------------------|-------------|--|
| LOG SHT        | 1    | RUN COMP. | <input checked="" type="checkbox"/> | RUN INCOMP. |  |
| No. STARTS     | 2    | ROUTED TO | CRASH CAB                           |             |  |
| TOTAL TIME     | 1:56 | OPER.     | [REDACTED]                          |             |  |
| DATE OF ACCEPT |      | OPER.     | [REDACTED]                          |             |  |

|                              |              |                |      |
|------------------------------|--------------|----------------|------|
| ECU S/N                      | CIT (T1) S/N | LOG SHT        | 1    |
| T/M CAL                      | 650 hp=      | No. STARTS     | 2    |
| COMP SEAL VENT ORIF DASH No. | -3-          | TOTAL TIME     | 1:56 |
|                              |              | DATE OF ACCEPT |      |