

## NATIONAL TRANSPORTATION SAFETY BOARD

Office of Aviation Safety Washington, D.C. 20594

September 1, 2016

Attachment 13 – British Airways Fire Cargo Forward Checklist

## **OPERATIONAL FACTORS**

**DCA15FA185** 



## [] FIRE CARGO FWD

Condition: Smoke is detected in the forward lower cargo compartment.

**Note:** If warning received on ground with cargo door open, do not accomplish checklist unless actual fire confirmed and all personnel clear. OM A refers.

1	FWD CARGO FIRE ARM		
	switch	Confirm	ARMED

- 2 CARGO FIRE DISCH switch . . . . . . . Push and hold for 1 second
- 3 Choose one:

♦On the ground:

Warning! Inform ground personnel
NOT to open any cargo door
until all passengers and crew
have exited the airplane and
fire fighting equipment is
nearby.

♦In flight:

▶▶Go to step 4

of the compartment.

4 LDG ALT selector . . . . . . . . . . . . . . . . PULL ON, set 8000 This minimizes extinguisher agent leakage out

5 Plan to land at the nearest suitable airport.

**Note:** Equipment cooling normal mode is inoperative. After 30 minutes of operation at low altitude and low cabin differential pressure, electronic equipment and displays may fail.

▼ Continued on next page ▼



	▼ FIRE CARGO FWD continued ▼			
6	Do <b>not</b> accomplish the following checklists:			
	EQUIP COOLING OVRD			
	LANDING ALTITUDE			
7	When leaving cruise altitude for landing:			
	LDG ALT selector Push off			
8	Checklist Complete Except Deferred Items			
	Deferred Items			
De	escent Checklist			
R	ecall Checked			
Ν	lotes			
Α	utobrake			
L	anding data VREF, Minimums			
A	pproach briefing Completed			
Ap	pproach Checklist			
A	Itimeters			
W	arning! Inform ground personnel NOT to open any cargo door after landing until all passengers and crew have exited the airplane and fire fighting equipment is nearby.			
Landing Checklist				

Cabin Report . . . . . . . . . . . . . . . . . . Received

Speedbrake . . . . . . . . . . . . . . . . . . ARMED

Landing gear . . . . . . . . . . . . DOWN