

Attachment 7
Test 001-11, 3/5/96

Materials contained in attachment 7

Test data tracking forms

Test engineer's notes

Test sequence

Time-history data plots for:

Conditions B1.39.0928.801-.803

Condition B1.39.0928.801.1

Condition B1.39.0928.802.1

Conditions B1.39.0928.805-.811

FLIGHT TEST DATA SHEET


IMPORTANT: DO NOT USE BLUE INK AS IT WILL NOT REPRODUCE FROM THE ORIGINAL

				Note: The Torque Tube measurements are very questionable.
TAPE ON	09:18:00			
	09:22:35	Confirmed 25 lbs on Fuel Pilot:		
	1:23:27	Hyd. ON (A&B)		
	09:24:01	A, B, & Standby cycled		
	09:24:12	A & B Only		
RI.39.0928.801	09:25:35	Cycle Rudder Pedals		
	1:25:42	L Rudder		
	1:25:46	Neutral		
	1:25:48	R Rudder		
	09:25:51	Neutral		
BI.39.0928.802	09:28:00	Dwell, 0.3Hz, 3° LR	40 lbs galling force	
	09:29:00	End		
BI.39.0928.811	09:30:45	Dwell, 1 Hz, 3° LR	to gell up bearing wdg	
	09:31:30	End		
BI.39.0928.811.1	09:34:40	Dwell, 1 Hz, 3° LR	same purpose	
	09:35:40	End		
BI.39.0928.801.1	09:37:25	Cycle Rudder Pedals	galling forces on the - standby PCW	
	1:37:29	L Rudder	input linkage are now ~60 lbs	
	1:37:32	Neutral		
	1:37:36	R Rudder		
	09:37:40	N		
BI.39.0928.802.1	09:38:56	Dwell, 0.3Hz, 3° LR		
	09:39:58	End		
BI.39.0928.803	09:40:10	Dwell, 0.3Hz, 1° LR		
	1:41:30	Manual Pedal Input		
	1:41:47	End Pedal		
	09:42:04	End Dwell		

SHEET	OF 2	TITLE	737-200 Rudder	MODEL	
RECORDER	D. Hugel	Ground Testing		AIRPLANE	
TEST NO.	001-11			DOC. NO.	
DATE	3/5/96			PAGE	



IMPORTANT: DO NOT USE BLUE INK AS IT WILL NOT REPRODUCE FROM THE ORIGINAL

SHEET 2 OF 2		TITLE 737-200 Radar	MODEL
RECORDER D. Nagel		Ground Testing	AIRPLANE
TEST NO. 001-11	51.1	BOEING	DOC. NO.
DATE 3/5/60			PAGE




03/05/96 1632		REQ LMR2-9132		737-200 RUDDER GRND TEST		737-200	
CALC		REVISED DATE		TIME HISTORY PLOT		PG309	
CHECK				CONDITION NO. B1-39-0928-802			
APR				TEST 001-11 TEST DATE 03/05/96		B1-39-0928	
APR				THE BOEING COMPANY		PRCE	


FORM 1
737-200, PG309, RUDDER SYSTEM GROUND TESTING





03/05/96 1632		REQ IAA2-9132		737-200 RUDDER GRND TEST		737-200	
CALC		REVISED		DATE		PC309	
CHECK						CONDITION NO. 81.39.0928.811	
APR						TEST 001-11 TEST DATE 03/05/96	
APR						THE BOEING COMPANY PAGE	


FORMAT 1
737-200, PC309, RUDDER SYSTEM GROUND TESTING








[illegible]




03/05/96 1632	REQ 1AA2.9132	737-200 RUDDER GRND TEST	737-200
CALC	REVISED DATE	TIME HISTORY PLOT	PG309
CHECK		CONDITION NO. B1.39.0928.802.1	
APR		TEST 001-11 TEST DATE 03/05/96	B1.39.0928
APR		THE BOEING COMPANY	PAGE


FORMAT 1
737-200. PG309. RUDDER SYSTEM GROUND TESTING



03/05/96 1632		REQ 1802.9132		737-200 RUDDER CRND TEST	
CALC	REVISED DATE	TIME HISTORY PLOT			
CHECK		CONDITION NO. B1.39-0928-803			
APR		TEST 001-11 TEST DATE 03/06/96			
APR		B1.39-0928			
APR		THE BOEING COMPANY			
PAGE		737-200			


FORMAT 1
737-200, PG309, RUDDER SYSTEM GROUND TESTING







03/05/96 1632	REQ 1002-9132	737-200 RUDDER GRND TEST	TIME HISTORY PLOT	PG309	737-200
CALC		REVISID	DATE		
CHECK					
APR					
APR					
APR					
CONDIION NO.	BI-39-0928-805	TEST DATE	03/05/96	BI-39-0928	PG309
THE BOEING COMPANY					


FORMAT 1
737-200, PG309, RUDDER SYSTEM GROUND TESTING






03/05/96	1632	REQ	1MR2.9132	737-200 RUDDER GRND TEST	737-200
		REVISED	DATE	TIME HISTORY PLOT	PG309
CALC					
CHECK				CONDITION NO. 81.39.0928.806	
APR				TEST 001-11 TEST DATE 03/05/96	81.39.0928
APR				THE BOEING COMPANY	PRGE



FORMAT 1
PG309. RUDDER SYSTEM GROUND TESTING
737-200.







03/05/96 1632	REQ 1RM2-9132	737-200 RUDDER GRND TEST	737-200
CALC	REVISED DATE	TIME HISTORY PLOT	PG309
CHECK		CONDITION NO. B1.39.0928.807	
RPR		TEST 001-11 TEST DATE 03/05/96	B1.39.0928
RPR		THE BOEING COMPANY	PRGE

FORMAT 1
737-200, PG309, RUDDER SYSTEM GROUND TESTING




03/05/96 1632	REQ INR2.9132	737-200 RUDDER GRND TEST	
	REVISED DATE	TIME HISTORY PLOT	
CALC		CONDITION NO.	81.39.0928.808
CHECK		TEST DATE	03/05/96
RPR		TEST NO.	001-11
		THE BOEING COMPANY	81.39.0928
		PRG	PG309


FORMAT 1
737-200, PG309, RUDDER SYSTEM GROUND TESTING



03/05/96 1632		REQ IAR2-9132		737-200 RUDDER GRND TEST TIME HISTORY PLOT		737-200 P0309	
CALC			REVISED	DATE	CONDITION NO. 81-39-0928-809 TEST 001-11 TEST DATE 03/05/96		81-39-0928 PAGE
CHECK							
APR					THE BOEING COMPANY		

FORMAT 1
737-200, PG309, RUDDER SYSTEM GROUND TESTING





03/05/96 1632	REQ IAA2-9132	737-200 RUDDER GRND TEST		737-200
CALC	REVISED DATE	TIME HISTORY PLOT		PG309
CHECK		CONDITION NO. 81-39-0928.810		
APR		TEST 001-11 TEST DATE 03/05/96		81-39-0928
APR		THE BOEING COMPANY		PAGE

FORMAT 1
737-200. PG309. RUDDER SYSTEM GROUND TESTING

SCHEDULED TESTING

T.I. #	Test Item Title
B1.39.0928	737-200 STANDBY RUDDER ACTUATOR FAILURE GROUND TEST - B

PURPOSE OF TEST

Jams of the standby rudder PCU control valve lever will be introduced on the ground. The resulting rudder control system operational characteristics will be investigated with various initial conditions and subsequent yaw damper, rudder pedal, and rudder trim inputs. The intent is to allow evaluation of these characteristics with an actual airplane's flight control system compliance, backlash, control valve flow, and pressure gains.

TEST PARAMETERS

- ☐ Hydraulic Power - Supplied to the A & B systems.
- ☐ Electrical Power - ON
- ☐ Nosewheel Steering - Disabled (either install nose gear steering lockout pin in nose gear steering depressurization valve per maintenance manual 32-00-01, or pull the nose gear air/ground circuit breaker on the P-6 panel).

TEST CONDITIONS

System Effects with a Galled Standby Rudder PCU Bearing

- A Standby PCU with a galled input linkage bearing will be installed. The bearing will be galled to about 60 pounds of input lever force.
- Set the Hydraulic System as noted.
- Minimize rudder pedal application with the galled bearing. Additional pedal cycles may increase the galling force and jeopardize the test results.

Condition No.	Hyd Pressure	Operation
☒ B1.39.0928.801	A & B	Cycle the rudder pedals through full deflection and note the system response.
☒ 802	A & B	Input a ± 3.0 degree yaw damper command at 0.3 Hz. Record the system response.
☒ 803	A & B	Input a ± 1.0 degree Yaw Damper Command at 0.3 Hz. Cycle the rudder pedals through full displacement during the frequency input. Record system response.
☒ 804	----	Confirm a simulated airload has been applied to the rudder trailing edge.
☒ 805	B & Stby	Cycle the rudder pedals through full deflection and note the system response.

<u>Condition No.</u>	<u>Hyd Pressure</u>	<u>Operation</u>
☒ 806	B & Stby	Input a ± 3.0 degree yaw damper command at 0.3 Hz. Record the system response.
☒ 807	B & Stby	Input a ± 1.0 degree Yaw Damper Command at 0.3 Hz. Cycle the rudder pedals through full displacement during the frequency input. Record system response.
☒ 808	A, B & Stby	Cycle the rudder pedals through full deflection and note the system response.
☒ 809	A, B & Stby	Input a ± 3.0 degree yaw damper command at 0.3 Hz. Record the system response.
☒ 810	A, B & Stby	Input a ± 1.0 degree Yaw Damper Command at 0.3 Hz. Cycle the rudder pedals through full displacement during the frequency input. Record system response.

ADDED
ADDITIONAL CONDITIONS

.801.1 A+B

.802.1 A+B

CYCLE THE RUDDER PEDALS
NOTE SYSTEM RESPONSE.

INPUT A ± 3.0 degree yaw damper
Command @ 0.3 Hz

G. PHILLIPS
4/26/96