

Risk Algorithm for Spectra Energy



February 2007
Rev 1 April, 2007
Rev 2 January, 2010
Rev 3 March, 2014



Suite 208, 1324 – 17th Avenue S.W.
Calgary, Alberta, Canada
T2T 5S8

Phone: (403) 547-8638
Fax: (403) 547-8628

Web: www.dynamicrisk.net

Table of Contents

1	COMMUNICATING RISK RESULTS.....	3
2	FAILURE LIKELIHOOD ASSESSMENT	4
2.1	EXTERNAL CORROSION	6
2.1.1	<i>Calculation of the Baseline Susceptibility Score</i>	6
2.1.2	<i>Calculation of the Integrity Assessment Mitigation Factor.....</i>	15
2.1.3	<i>Calculation of the Stray Current / Interference Factor</i>	17
2.2	SCC	18
2.2.1	<i>Near-neutral pH SCC Score</i>	18
2.2.2	<i>High pH SCC Score</i>	26
2.3	3RD PARTY DAMAGE	33
2.3.1	<i>Hit Susceptibility Score.....</i>	33
2.3.2	<i>Scoring for Failure Susceptibility, Given a Hit (S_f in the 3rd Party Damage Score Equation)</i>	42
2.4	INTERNAL CORROSION	47
2.4.1	<i>Baseline Internal Corrosion Score (SB_{IC}) (0-10).....</i>	47
2.4.2	<i>Mitigation Multiplication Factor (MMF) (0-1).....</i>	60
2.5	MANUFACTURING DEFECTS	62
2.5.1	<i>Hard Spot Score (0 – 10).....</i>	62
2.5.2	<i>Seam Defect Score (Score Range: 0-10).....</i>	65
2.6	CONSTRUCTION THREAT	67
2.6.1	<i>Wrinkle Bend Susceptibility Factor – [WB (0 or 1)]</i>	68
2.6.2	<i>Bend Angle Factor – [F_θ(0 to 1)].....</i>	68
2.6.3	<i>Coupling Susceptibility Factor – [C (0 or 1)]</i>	68
2.6.4	<i>Coupling Reinforcement Factor – [F_{CR} (0 to 10)].....</i>	68
2.6.5	<i>Welding Defect Susceptibility Factor – [W (0 to 10)]</i>	69
2.6.6	<i>Girth Weld Reinforcement Factor – [F_{WR} (0 to 1)]</i>	70
2.6.7	<i>X-Ray Inspection Factor – [F_{XR} (0 to 1)]</i>	71
2.6.8	<i>Pressure Cycling Factor – [F_{AP} (1 to 2)].....</i>	71
2.6.9	<i>Ground Movement Factor – [(GMF (0 to 10)]......</i>	71
2.7	EQUIPMENT FAILURE	72
2.8	WEATHER – OUTSIDE FORCE THREATS.....	73
2.8.1	<i>Lightening Strike Susceptibility Score (1-10)</i>	73
2.8.2	<i>Geotechnical Threat Score</i>	75
2.9	INCORRECT OPERATIONS	78
3	CONSEQUENCE ASSESSMENT	79
3.1	SAFETY	80
3.2	ECONOMIC LOSS	83
3.2.1	<i>Determination of Repair Costs</i>	85
3.2.2	<i>Determination of Public Damage Costs</i>	86
3.2.3	<i>Determination of Gas Loss \$ Costs</i>	87
3.2.4	<i>Outage Loss Score (1-10).....</i>	88
3.3	ENVIRONMENTAL LOSS	89
3.3.1	<i>Impact Radius Score (S_R) (1 to 10).....</i>	89
3.3.2	<i>Environmental Land Use Score (L) (1 – 10).....</i>	90
	APPENDIX A – DERIVATION OF SAFETY CONSEQUENCE SCORES	91
	APPENDIX B – DERIVATION OF PUBLIC DAMAGE COSTS	97

Risk Algorithm for Spectra Energy



Rev 5, January 2017



Suite 1110, 333 – 11th Avenue S.W.
Calgary, Alberta, Canada
T2R 1L9
Phone: (403) 547-8638

Waterway Plaza Two, Suite 250
10001 Woodloch Forest Drive
The Woodlands, TX 77380
Phone: (832) 482-0606
www.dynamicrisk.net

Table of Contents

1	COMMUNICATING RISK RESULTS.....	5
2	FAILURE LIKELIHOOD ASSESSMENT.....	6
2.1	EXTERNAL CORROSION.....	8
2.1.1	<i>Method 1 – No ILI Data Available</i>	8
	Material Type Score.....	9
	Calculation of the Baseline Susceptibility Score.....	9
	Calculation of the Integrity Assessment Factor.....	18
	Calculation of the Stray Current/Interference Factor	19
2.1.2	<i>Method 2 – ILI Data Available</i>	20
	Calculation of External Corrosion POE	22
2.2	SCC	29
2.2.1	<i>SCC Susceptibility Analysis</i>	30
2.2.2	<i>SCC Scoring for Susceptible Segments (C)</i>	31
2.3	3RD PARTY DAMAGE	33
2.3.1	<i>Hit Susceptibility Score.....</i>	33
2.3.2	<i>Scoring for Failure Susceptibility, Given a Hit (S_f in the 3rd Party Damage Score Equation)</i>	42
2.4	INTERNAL CORROSION.....	47
2.4.1	<i>Baseline Internal Corrosion Score (SB_{IC}) (0-10).....</i>	47
2.4.2	<i>Mitigation Multiplication Factor (MMF) (0-1).....</i>	60
2.5	MANUFACTURING DEFECTS	62
2.5.1	<i>Hard Spot Score (0 – 10).....</i>	62
2.5.2	<i>Seam Defect Score (Score Range: 0-10).....</i>	66
2.6	CONSTRUCTION THREAT.....	68
2.6.1	<i>Wrinkle Bend Susceptibility Factor – [WB (0 or 1)]</i>	69
2.6.2	<i>Bend Angle Factor – [F_θ(0 to 1)].....</i>	69
2.6.3	<i>Coupling Susceptibility Factor – [C (0 or 1)]</i>	69
2.6.4	<i>Coupling Reinforcement Factor – [F_{CR} (0 to 10)]</i>	69
2.6.5	<i>Welding Defect Susceptibility Factor – [W (0 to 10)]</i>	70
2.6.6	<i>Girth Weld Reinforcement Factor – [F_{WR} (0 to 1)]</i>	71
2.6.7	<i>X-Ray Inspection Factor – [F_{XR} (0 to 1)]</i>	72
2.6.8	<i>Pressure Cycling Factor – [F_{AP} (1 to 2)].....</i>	72
2.6.9	<i>Ground Movement Factor – [(GMF (0 to 10)].....</i>	72
2.7	EQUIPMENT FAILURE	73
2.8	WEATHER – OUTSIDE FORCE THREATS.....	74
2.8.1	<i>Lightening Strike Susceptibility Score (1-10)</i>	74
2.8.2	<i>Geotechnical Threat Score</i>	76
2.9	INCORRECT OPERATIONS	79
3	CONSEQUENCE ASSESSMENT	80
3.1	SAFETY	81
3.2	ECONOMIC LOSS	83
3.2.1	<i>Determination of Repair Costs</i>	85
3.2.2	<i>Determination of Public Damage Costs</i>	86
3.2.3	<i>Determination of Gas Loss \$ Costs</i>	87
3.2.4	<i>Outage Loss Score (1-10).....</i>	88
3.3	ENVIRONMENTAL LOSS	89
3.3.1	<i>Impact Radius Score (S_R) (1 to 10)</i>	89
3.3.2	<i>Environmental Land Use Score (L) (1 – 10).....</i>	90
APPENDIX A – DERIVATION OF SAFETY CONSEQUENCE SCORES		91
APPENDIX B – DERIVATION OF PUBLIC DAMAGE COSTS		97