

EQUAL ACCESS INSPECTION

RED LINE FLEET

DATE: 7-23-21

CAR NUMBER: 1757

Platform Height and Gap Inspection

Place threshold gauge onto and inside the running rail, keeping gauge level to floor. Use gauge to inspect door threshold height and gap by using the colors on the measurement-sliding device. Green area inspects the gap, red area inspects the height.

DOOR	PLATFORM GAP MEASUREMENT		PLATFORM HEIGHT MEASUREMENT	
	GO	NO GO	GO	NO GO
A	✓		✓	
B	✓		✓	
C	✓		✓	
D	✓		✓	
E	✓		✓	
F	✓		✓	
G				
H				

PA Sound Level Inspection

Place the sound level meter in the center of the car, five feet above floor for test. Activate door close chime, recording the maximum (dBA) level on the meter.

Maximum level recorded (dBA) 68

Enter Y-EAI code and 30 minutes labor on each car, file with Mileage Inspection sheet.

Task No.	Description	Task	Initials	Task No.	Description	Task	Initials
Air & Electric / Couplers (continued)				Car Body Inspection Sections 8,9,10			
5d.	Gov. Pressure Switch; Gov. Off/On PSI <u>148</u> / <u>130</u>	V,F,A,X	PII	Interior			
5.e.	Compressor Off Time: <u>5</u> min <u>08</u> sec	V,F,X		8	Interior Car body	V	PII
5.f.	Intercooler Pressure: <u>40</u> PSI	V,F,X,P		8.a.	Glass and Window Gaskets	V,F,R	
5.g.	Drain Valve / Tanks (purge)	V,F,P		8.b.	Lighting: Passenger, Cab, Emergency	V,F,R	
5.h.	Heaters (compressor and drain valve)	V,F		8.c.	Horns, Buzzers and Bells	V,F	
5.i.	Wiring, Piping, Hoses	V,F		8.d.	Windshield Wiper and Blade	V,F,R	
5.j.	Dryers / Filters	V,F		8.e.	Cab Heat and Defroster	V,F,C	
5.k.	Cineston and Deadman Operation, Switch Springs, Cineston Contact Tips	V,F,C,R		8.f.	Radio, PA, Intercom and PEI	V,F	
5.l.	Console Gauges	V,F,A,R		8.g.	Operator's Seat, Visor and Curtains	V,F,R	
5.m.	Brake Pressures: Brake Valves SAP <u>72</u> PSI BP <u>111</u> PSI MIN <u>16</u> PSI MAX <u>34</u> PSI EMERG <u>44</u> PSI SNOW <u>8</u> PSI INSHOT <u>10</u> PSI	V,F,A,X		8.h.	Sash Windows	V,F,R	
5.n.	Air Spring /Leveling Valves, Pressures #1 <u>21</u> PSI #2cs <u>20</u> PSI #2ocs <u>20</u> PSI	V,F,A,X	8.i.	Console Switches and Labels	V,F,R		
Auxiliary Electrics				Exterior			
6	Converter: Gaskets, Covers, Hardware	V,F	9	Exterior Car body	V		
6.a.	Electronic Card Rack / Controls	V,F	9.a.	Destination Signs Roll; Interior / Exterior	V,F,R		
6.b.	External Resistors: Cabling	V	9.b.	Marker Lights	V,F,R		
6.c.	Output Voltage MG / Converter <u>37.7</u> volts.	V,F,A,X	9.c.	ATP Operation (amber) Lights	V,F,R		
6.d.	Battery Enclosure, Cover, Hardware	V,F,C	9.d.	Snow brake / Sleet Scraper (amber) Lights	V,F,R		
6.e.	Battery Vent Caps, Terminals, Cables, Trays	V,F,C	9.e.	End Gate, Springs and Straps	V,F		
6.f.	Battery Cells, Excessive Corrosion	V,F,R,C	9.f.	Handbrake, Door Pilot, and Individual Door Leaf Lights	V,F,R		
6.g.	Battery Electrolyte Level (deionized water) Battery <u>32.3</u> volts.	V,F,R,X	Doors				
6.h.	Snow Brake, Sleet Scraper (amber) Lights	V,F,R	10	Door Operation	V,F		
Couplers				Doors (Continued)			
7	Electric Coupler Boxes and Buttons	V,F,R,C	10.q.	Door Safety Ground Test: Pin #19: <u>0.3</u> Ω Pin #20: <u>0.3</u> Ω	V,F,X	PII	
7.a.	Air Control Valves (EP Box)	V,F	10.r.	No Motion Sensors B-C AXLE 1: <u>447</u> Ω AXLE 2: <u>446</u> Ω AXLE 3: <u>446</u> Ω E-F AXLE 4: <u>447</u> Ω	V,F,X		
7.b.	Centering Device and Negating Valve	V,F,L	10.s.	ATO Readings ASR: <u>NA</u> Ω FRG: <u>NA</u> Ω Receiver Coil Reading: <u>NA</u> Ω	V,F,X		
7.c.	Drum Switch	V,F	Equal Access Inspection				
7.d.	Draft Gears	V,F	11	Complete Per Procedure Using EAI Form Filed With This Mileage Inspection Form	T		
7.e.	Coupler Head, Height Adjuster, Gauge	V,F,L	Car Body Inspector Initial Sections 8,9,10,11				
7.f.	Manual Uncouple Lever	V,F,L	Signature: <u>PII</u> Emp. No: <u>141171</u>				
7.g.	Drawbar Yoke, Anchor and Casting	V,F					
7.h.	Shear Pins and Safety Wire	V,R					
7.i.	Radial Carrier	V,F,L					
7.j.	Cables, Clamps, Cannon Plugs (safety wire)	V,R					
7.k.	Air Pipes, Hoses, Clamps and Hardware	V,R					
Air & Electric / Couplers Inspector Initial Section 5,6,7							
Signature: <u>PII</u> Emp. No: <u>73560</u>							

Task No.	Description	Task	Initials
Doors (Continued)			
10.q.	Door Safety Ground Test: Pin #19: <u>0.3</u> Ω Pin #20: <u>0.3</u> Ω	V,F,X	PII
10.r.	No Motion Sensors B-C AXLE 1: <u>447</u> Ω AXLE 2: <u>446</u> Ω AXLE 3: <u>446</u> Ω E-F AXLE 4: <u>447</u> Ω	V,F,X	
10.s.	ATO Readings ASR: <u>NA</u> Ω FRG: <u>NA</u> Ω Receiver Coil Reading: <u>NA</u> Ω	V,F,X	
Equal Access Inspection			
11	Complete Per Procedure Using EAI Form Filed With This Mileage Inspection Form	T	
Car Body Inspector Initial Sections 8,9,10,11			
Signature: <u>PII</u> Emp. No: <u>141171</u>			

Part	Stock Number	Quantit
Contact Shoe	025-96-001	
Contact Shoe Shunt	025-74-090	
Contact Shoe Stud	025-96-010	
Ice Scraping Contact Shoe	030-74-118	
Shoe Fuse #1&2 Car	025-74-509	
Brake Shoe #1&2 Car	010-96-029	1
Sleet Scraper Blade	025-97-001	
Sleet Scraper Blade	025-97-002	
Ground Brush Holder #1&2 Car	033-74-010	
Ground Brush #1&2 Car	035-74-277	4
Ground Brush Spring #1&2 Car	033-74-007	
Ground Brush Holder Insert #1&2 Car	033-74-008	
Ground Brush Cover #1&2 Car	035-07-167	
Traction Motor Filter	030-80-132	8
Traction Motor Brush	025-04-240	
Hitch Pin, (Handbrake Type)	420-71-020	
Picture Window	023-11-285	
Stationary Sash Window, #1 Car	023-11-314	
Sliding Sash Window, #1 Car	023-11-315	
Stationary Sash Window, #2 Car	026-74-055	
Sliding Sash Window, #2 Car	026-74-056	
Door Glass	023-11-295	
Fire Extinguisher, 10 lb.	024-10-078	
Fire Extinguisher, 20 lb.	024-10-075	
Frangible Pins, #1 Car	034-96-131	1
Frangible Pins, #2 Car	026-74-001	
Fluorescent Tube T-12 48"	311-55-654	4
Lamp Ballast	025-74-113	
Fluorescent Tube T-12 36"	311-55-643	
Fluorescent Tube T-12 18"	311-55-608	
Fluorescent Tube T-12 24"	311-55-615	
Pilot Light, Double Contact	025-45-837	
Pilot Light, Single Contact	025-45-022	
Bulb, Duplex Gauge	025-45-849	
Shatterproof Air Gauge Lens	032-28-046	
Drawbar Button #1 Car	026-96-500	
Drawbar Button #2 Car	025-23-023	
Hitch Pin (Leveling Valve Type)	032-55-001	
D4 Intake Filter	032-11-033	1
D4 Comp. Brushes	032-11-251	
Interlock Arm Contacts	035-01-191	
Cam Switch Tip, Moveable	035-80-001	3
Cam Switch Tip, Fixed	035-90-002	3
Contactor Tip, Copper	035-80-005	3
Contactor Tip, Silver	035-65-319	4
Cam Switch Shunts	035-01-154	4
Line Switch Tip	035-01-105	2
E-Brake Lever Plastic Tab	026-96-115	
Bearing Temperature Tags	024-03-030	
Enter Stock no. and Qty. into Work Order via Scan Tool		

Work Order ID: 5813

Car.No. 1757 Date: 7-23-21
 Current-Life-Mileage: 1740584
 Last Inspection Life Mileage: 1732647
 Mileage Since Last Inspected: 7937

Deferred Priority Codes: A-Hold for Repair, B-Schedule for Repair

[illegible]

#1 Wheel Size: 27 1/2 Condition: OK #2 Wheel Size: 27 1/2 Condition: OK
#3 Wheel Size: 28 Condition: OK #4 Wheel Size: 27 1/2 Condition: OK

Foreperson's Signature PII Employee Number: 66503

Initial Sections 2.d,e,f. and 10.p.

Rev1 10-19

**MBTA REDLINE
#1 and #2 CAR**

INSPECTION FORM

CAR NO. 1757 **DATE:** 7-23-21
MILEAGE SINCE LAST INSPECTED: 7937

Tasks:	<i>V-Visual</i>	<i>L-Lubricate</i>	<i>C-Clean</i>
	<i>F-Verify proper function</i>	<i>R-Replace as needed</i>	<i>P-Purge</i>
	<i>A-Adjust to proper setting</i>	<i>X-Record values</i>	<i>T-Test</i>

Note to Inspection Staff: If any problems are noted during your inspection please place a circle around the task number of the problem area. These circled items will then be transferred to deferred items list for further attention.

Task No.	Description	Task	Initials	Task No.	Description	Task	Initials
Truck Inspection Sections 1,2,3				Truck Inspector Initial Sections 1,2,3			
1	Truck Frame	V	P11	Signature: [Redacted] Emp. No: 73531			
1.a	King Pin and Hardware	V,F		Propulsion Section 4			
1.b	Hoses, Piping and Clamps	V,F		4	Propulsion Enclosure, Covers, Gaskets	V,F,C	P11
1.c	Cables, Ground Straps	V,F,R		4.a	Propulsion Relays and Tips	V,F,C,R	
1.d	Bearer Surfaces ; Center and Side	V,F		4.b	Cables, Wiring, Connections.	V,F,A	
1.e	Journal Springs	V		4.c	Line Switch Coil-Blowout, Overload	V,F,A,R,C	
1.f	Pedestal Bolts	V,A		4.d	Line Switch Tips-Main, Overload	V,F,A,R,C	
1.g	Bolster Anchors Shimming and Bolts	V,F		4.e	Operation of all Mag Valves	V,F,L	
1.h	Dampers, Snubbers and Shocks	V,F		4.f	SPC Tips, Cam Rollers, Shunts	V,F,A,R,C	
1.i	Hand Brake Linkage	V,F,A,L,R		4.g	SPC Interlock Tips	V,F,A,R,C	
1.j	Shoe Beams, Flash Shields (hardware)	V,F,A		4.h	PBC Tips, Cam Rollers, Shunts	V,F,A,R,C	
1.k	Collector Paddles (height and tension)	V,F,A,R		4.i	Reverser Segments and Insulators	V,F,R,C	
1.l	Shoe Shunts, Fuses and Hardware	V,F,A,R		4.j	Reverser Interlock Tips	V,F,A,R,C	
1.m	Sleet Scrapers, Blades, Hoses and Hardware	V,F,A,L,R		4.k	Contactors Tips and Shunts	V,F,A,R,C	
1.n	Trips, Hoses and Hardware	V,F,A,L		4.l	Contactors Interlock Tips, Shunts, Arms	V,F,A,R,C	
1.o	Brake Units, Shoes, Keys, Piping and Hoses	V,F,A,L,R		4.m	Electronic Cards	V,F,R	
1.p	Brake Cutout, Linkage and Hardware	V,F,L		4.n	Cam Controller, Switches, Tips and Shunts	V,F,A,R,C	
1.q	ATP Receiver Coils and Hardware	V,C		4.o	Mag Amp Wiring and Connections	V,F	
Gear Units				4.p	Field Forcing Panel, Fuse, Wiring	V,F	
2	Gears	V		4.q	Field Shunt Resistors, Fuse, Wiring	V,F,R	
2.a	Gear Oil	V,R		4.r	Inshot Valve Operation	V,F,A	
2.b	Covers, Plugs and Breathers	V,C		4.s	Propulsion Ground Fault Unit (#1 Car)	V,F,R	
2.c	Bearings, Wear Plates, Temperature Tag	V,L,R		4.t	Propulsion Overload Light	V,F,R	
2.d	Wheels	V		4.u	Propulsion Megger Reading Case: 866 Meg Ω	V,F,X	
2.e	Wheel Flanges (gauge)	V		4.v	Contact Shoe Megger Reading Shoe: 275.2 Meg Ω	V,F,X	
2.f	Wheel Diameter	V,X		4.w	Braking Grids and Cables	V	
2.g	Axles (Wheel Back to Back Measurement) 1: 43 3/8 2: 53 3/8 3: 53 3/8 4: 53 3/8	V,X		4.x	Propulsion Air Supply, Hoses and Piping	V,F	
2.h	Axle Ground Brushes and Springs	V,F,R		4.y	Sequence Controls With Box and Cineston	V,F	
2.i	Axle Ground Ring Signature: [Redacted]	V		4.z	Notch car with 600v "Think Safety"	V,F	
2.j	Axle Ground Housings and Hardware	V,F,R		Propulsion Inspector Initial Section 4			
2.k	Axle Ground Cables Straps and Jumpers	V,F,A,R		Signature: [Redacted] Emp. No: 503921			
Traction Motors				Air & Electric / Couplers Inspection Sections 5,6,7			
3	Motors	V		5	Air System	V	P11
3.a	Motor Filters, Covers	V,F,R		5.a	Compressor Motor Brushes	V,F,C,R	
3.b	Motor Brushes, Brush holders	V,F,R		5.b	Air Compressor Unit, Oil Level	V,F,L,R	
3.c	Horizontal Mounting Bolts and Bushings	V		5.c	Compressor Control Box and Tips	V,F,R	
3.d	Vertical Mounting Bolts and Bushings	V					
3.e	Safety Brackets and Hardware	V,F					
3.f	Motor to Gear Unit Bolts (torque) 150 ft.-lbs.	V,A					
3.g	Motor Cables and Clamps	V,F					
3.h	Motor Clamshell Leads	V					
3.i	Clamshell Contacts and Hardware	V					

MBTA REDLINE

#1 and #2 CAR

CAR NO.

1757

DATE:

10/21/21

INSPECTION FORM

MILEAGE SINCE LAST INSPECTED:

7902

Tasks:	V-Visual	L-Lubricate	C-Clean
	F-Verify proper function	R-Replace as needed	P-Purge
	A-Adjust to proper setting	X-Record values	T-Test

Note to Inspection Staff: If any problems are noted during your inspection please place a circle around the task number of the problem area. These circled items will then be transferred to deferred items list for further attention.

Task No.	Description	Task	Initials	Task No.	Description	Task	Initials
Truck Inspection Sections 1,2,3				Truck Inspector Initial Sections 1,2,3			
1	Truck Frame	V	PII	Signature: PII Emp. No: 694139			
1.a.	King Pin and Hardware	V,F		Propulsion Section 4			
1.b.	Hoses, Piping and Clamps	V,F		4	Propulsion Enclosure, Covers, Gaskets	V,F,C	PII
1.c.	Cables, Ground Straps	V,F,R		4.a.	Propulsion Relays and Tips	V,F,C,R	
1.d.	Bearer Surfaces ; Center and Side	V,F		4.b.	Cables, Wiring, Connections	V,F,A	
1.e.	Journal Springs	V		4.c.	Line Switch Coil-Blowout, Overload	V,F,A,R,C	
1.f.	Pedestal Bolts	V,A		4.d.	Line Switch Tips-Main, Overload	V,F,A,R,C	
1.g.	Bolster Anchors Shimming and Bolts	V,F		4.e.	Operation of all Mag Valves	V,F,L	
1.h.	Dampers, Snubbers and Shocks	V,F		4.f.	SPC Tips, Cam Rollers, Shunts	V,F,A,R,C	
1.i.	Hand Brake Linkage	V,F,A,L,R		4.g.	SPC Interlock Tips	V,F,A,R,C	
1.j.	Shoe Beams, Flash Shields (hardware)	V,F,A		4.h.	PBC Tips, Cam Rollers, Shunts	V,F,A,R,C	
1.k.	Collector Paddles (height and tension)	V,F,A,R		4.i.	Reverser Segments and Insulators	V,F,R,C	
1.l.	Shoe Shunts, Fuses and Hardware	V,F,A,R		4.j.	Reverser Interlock Tips	V,F,A,R,C	
1.m.	Sleet Scrapers, Blades, Hoses and Hardware	V,F,A,L,R		4.k.	Contactor Tips and Shunts	V,F,A,R,C	
1.n.	Trips, Hoses and Hardware	V,F,A,L		4.l.	Contactor Interlock Tips, Shunts, Arms	V,F,A,R,C	
1.o.	Brake Units, Shoes, Keys, Piping and Hoses	V,F,A,L,R		4.m.	Electronic Cards	V,F,R	
1.p.	Brake Cutout, Linkage and Hardware	V,F,L		4.n.	Cam Controller, Switches, Tips and Shunts	V,F,A,R,C	
1.q.	ATP Receiver Coils and Hardware	V,C		4.o.	Mag Amp Wiring and Connections	V,F	
Gear Units				4.p.	Field Forcing Panel, Fuse, Wiring	V,F	
2	Gears	V		4.q.	Field Shunt Resistors, Fuse, Wiring	V,F,R	
2.a.	Gear Oil	V,R		4.r.	Inshot Valve Operation	V,F,A	
2.b.	Covers, Plugs and Breathers	V,C		4.s.	Propulsion Ground Fault Unit (#1 Car)	V,F,R	
2.c.	Bearings, Wear Plates, Temperature Tag	V,L,R		4.t.	Propulsion Overload Light	V,F,R	
2.d.	Wheels	V		4.u.	Propulsion Megger Reading	V,F,X	
2.e.	Wheel Flanges (gauge)	V		Case: .7 Meg Ω			
2.f.	Wheel Diameter	V,X		4.v.	Contact Shoe Megger Reading	V,F,X	
2.g.	Axles (Wheel Back to Back Measurement)	V,X		Shoe: 700F Meg Ω			
	1: 53 3/8 2: 53 3/8			4.w.	Braking Grids and Cables	V	
	3: 53 3/8 4: 53 3/8			4.x.	Propulsion Air Supply, Hoses and Piping	V,F	
2.h.	Axle Ground Brushes and Springs	V,F,R		4.y.	Sequence Controls With Box and Cineston	V,F	
2.i.	Axle Ground Ring	V		4.z.	Notch car with 600v "Think Safety"	V,F	
	Signature: PII			Propulsion Inspector Initial Section 4			
2.j.	Axle Ground Housings and Hardware	V,F,R		Signature: PII Emp. No: 66311			
2.k.	Axle Ground Cables Straps and Jumpers	V,F,A,R		Air & Electric / Couplers Inspection Sections 5,6,7			
Traction Motors				5	Air System	V	PII
3	Motors	V		5.a.	Compressor Motor Brushes	V,F,C,R	
3.a.	Motor Filters, Covers	V,F,R		5.b.	Air Compressor Unit, Oil Level	V,F,L,R	
3.b.	Motor Brushes, Brush holders	V,F,R		5.c.	Compressor Control Box and Tips	V,F,R	
3.c.	Horizontal Mounting Bolts and Bushings	V					
3.d.	Vertical Mounting Bolts and Bushings	V					
3.e.	Safety Brackets and Hardware	V,F					
3.f.	Motor to Gear Unit Bolts (torque) 150 ft-lbs.	V,A					
3.g.	Motor Cables and Clamps	V,F					
3.h.	Motor Clamshell Leads	V					
3.i.	Clamshell Contacts and Hardware	V					

Task No.	Description	Task	Initials	Task No.	Description	Task	Initials
Air & Electric / Couplers (continued)				Car Body Inspection Sections 8,9,10			
5d.	Gov. Pressure Switch: Gov. Off/On PSI <u>127</u> / <u>149</u>	V,F,A,X	P11	Interior			
5.e.	Compressor Off Time: <u>7</u> min <u>00</u> sec	V,F,X		8	Interior Car body	V	P11
5.f.	Intercooler Pressure: <u>40</u> PSI	V,F,X,P		8.a.	Glass and Window Gaskets	V,F,R	
5.g.	Drain Valve / Tanks (purge)	V,F,P		8.b.	Lighting; Passenger, Cab, Emergency	V,F,R	
5.h.	Heaters (compressor and drain valve)	V,F		8.c.	Horns, Buzzers and Bells	V,F	
5.i.	Wiring, Piping, Hoses	V,F		8.d.	Windshield Wiper and Blade	V,F,R	
5.j.	Dryers / Filters	V,F		8.e.	Cab Heat and Defroster	V,F,C	
5.k.	Cineston and Deadman Operation, Switch Springs, Cineston Contact Tips	V,F,C,R		8.f.	Radio, PA, Intercom and PEI	V,F	
5.l.	Console Gauges	V,F,A,R		8.g.	Operator's Seat, Visor and Curtains	V,F,R	
5.m.	Brake Pressures: Brake Valves	V,F,A,X		8.h.	Sash Windows	V,F,R	
	SAP <u>72</u> PSI			8.i.	Console Switches and Labels	V,F,R	
	BP <u>109</u> PSI			8.j.	Instruction Decals and Advertising Signs	V,F	
	MIN <u>15</u> PSI			8.k.	Safety Equipment: Ladder, 4 Shoe Hooks, Shoe Lifter, 2 Fire Extinguishers, Evac Chair/even car, Rope/Ty-Rap®	V,F,R	
	MAX <u>86</u> PSI			8.l.	Low Voltage Circuit Breaker Panel	V	
	EMERG <u>44</u> PSI			8.m.	Stanchions and Grab Handles	V,F	
	SNOW <u>8</u> PSI			8.n.	Passenger Seats	V,R	
	INSHOT <u>10</u> PSI			8.o.	Passenger Emergency Pulls and Tabs	V,F,R	
5.n.	Air Spring /Leveling Valves, Pressures	V,F,A,X		8.p.	Interior Panels and Flooring	V	
	#1 <u>16</u> PSI			8.q.	Trip Cutout, Horn Cutout and Air Spring Cutouts	V,F	
	#2cs <u>16</u> PSI			8.r.	Handbrake Ratchet and Micro Switch	V,F,L	
	#2ocs <u>16</u> PSI			8.s.	Destination Signs and Lighting	V,F,R	
Auxiliary Electrics				Exterior			
6	Converter: Gaskets, Covers, Hardware	V,F		9	Exterior Car body	V	
6.a.	Electronic Card Rack / Controls	V,F		9.a.	Destination Signs Roll; Interior / Exterior	V,F,R	
6.b.	External Resistors: Cabling	V		9.b.	Marker Lights	V,F,R	
6.c.	Output Voltage MG / Converter <u>37.46</u> volts.	V,F,A,X		9.c.	ATP Operation (amber) Lights	V,F,R	
6.d.	Battery Enclosure, Cover, Hardware	V,F,C		9.d.	Snow brake / Sleet Scraper (amber) Lights	V,F,R	
6.e.	Battery Vent Caps, Terminals, Cables, Trays	V,F,C		9.e.	End Gate, Springs and Straps	V,F	
6.f.	Battery Cells, Excessive Corrosion	V,F,R,C		9.f.	Handbrake, Door Pilot, and Individual Door Leaf Lights	V,F,R	
6.g.	Battery Electrolyte Level (deionized water) Battery <u>32.22</u> volts.	V,F,R,X		Doors			
6.h.	Snow Brake, Sleet Scraper (amber) Lights	V,F,R		10	Door Operation	V,F	
Couplers				10.a.	Door Control Relay Panel; Relays & Wiring	V,F,C,R	
7	Electric Coupler Boxes and Buttons	V,F,R,C		10.b.	Door Open & Close Toggle Switches	V,F,R	
7.a.	Air Control Valves (EP Box)	V,F		10.c.	Door Set-up Switch	V,F	
7.b.	Centering Device and Negating Valve	V,F,L		10.d.	Door By-Pass Switch	V,F	
7.c.	Drum Switch	V,F		10.e.	Door Engine Operators	V,F,A	
7.d.	Draft Gears	V,F		10.f.	Obstruction Micro Switches	V,F,A	
7.e.	Coupler Head, Height Adjuster, Gauge	V,F,L		10.g.	Door Locking / Unlocking Assemblies	V,F,A,L	
7.f.	Manual Uncouple Lever	V,F,L		10.h.	Door Obstruction; Test Top, Middle and Bottom	V,F,A	
7.g.	Drawbar Yoke, Anchor and Casting	V,F		10.i.	Door Leaf Alignment	V,F,A	
7.h.	Shear Pins and Safety Wire	V,R		10.j.	Door Actuators, Tracks, Rollers and Shims	V,F	
7.i.	Radial Carrier	V,F,L		10.k.	Door Nosing Rubbers, Alignment, Gap and Condition	V,F,A	
7.j.	Cables, Clamps, Cannon Plugs (safety wire)	V,R		10.l.	Door Emergency Release Handles	V,F,A	
7.k.	Air Pipes, Hoses, Clamps and Hardware	V,R		10.m.	End Door (track, lock and latch)	V,F,L,C	
Air & Electric / Couplers Inspector Initial Section 5,6,7					<u>#25</u>		
Signature: <u>P11</u>				10.o.	Cab Door (jamb, hinges and lock)	V,F,L,C	
No. <u>73601</u>				10.p.	Spin Slide System	V,F	

Task No.	Description	Task	Initials
Doors (Continued)			
10.q.	Door Safety Ground Test: Pin #19: <u>3</u> Ω Pin #20: <u>4</u> Ω	V,F,X	PII
10.r.	No Motion Sensors B-C AXLE 1: <u>431</u> Ω AXLE 2: <u>431</u> Ω AXLE 3: <u>432</u> Ω E-F AXLE 4: <u>431</u> Ω	V,F,X	
10.s.	ATO Readings ASR: <u>/</u> Ω FRG: <u>/</u> Ω Receiver Coil Reading: <u>/</u> Ω	V,F,X	
Equal Access Inspection			
11	Complete Per Procedure Using EAI Form Filed With This Mileage Inspection Form	T	
Car Body Inspector Initial Sections 8,9,10,11			
Signature: <u>PII</u> Emp. No: <u>66422</u>			

Part	Stock Number	Quantity
Contact Shoe	025-96-001	
Contact Shoe Shunt	025-74-090	
Contact Shoe Stud	025-96-010	
Ice Scraping Contact Shoe	030-74-118	2
Shoe Fuse #1&2 Car	025-74-509	
Brake Shoe #1&2 Car	010-96-029	
Sleet Scraper Blade	025-97-001	
Sleet Scraper Blade	025-97-002	
Ground Brush Holder #1&2 Car	033-74-010	
Ground Brush #1&2 Car	035-74-277	
Ground Brush Spring #1&2 Car	033-74-007	
Ground Brush Holder Insert #1&2 Car	033-74-008	
Ground Brush Cover #1&2 Car	035-07-167	
Traction Motor Filter	030-80-132	8
Traction Motor Brush	025-04-240	8
Hitch Pin, (Handbrake Type)	420-71-020	
Picture Window	023-11-285	
Stationary Sash Window, #1 Car	023-11-314	
Sliding Sash Window, #1 Car	023-11-315	
Stationary Sash Window, #2 Car	026-74-055	
Sliding Sash Window, #2 Car	026-74-056	
Door Glass	023-11-295	
Fire Extinguisher, 10 lb.	024-10-078	
Fire Extinguisher, 20 lb.	024-10-075	
Frangible Pins, #1 Car	034-96-131	
Frangible Pins, #2 Car	026-74-001	
Fluorescent Tube T-12 48"	311-55-654	
Lamp Ballast	025-74-113	
Fluorescent Tube T-12 36"	311-55-643	
Fluorescent Tube T-12 18"	311-55-608	
Fluorescent Tube T-12 24"	311-55-615	
Pilot Light, Double Contact	025-45-837	
Pilot Light, Single Contact	025-45-022	
Bulb, Duplex Gauge	025-45-849	
Shatterproof Air Gauge Lens	032-28-046	
Drawbar Button # 1 Car	026-96-500	
Drawbar Button # 2 Car	025-23-023	
Hitch Pin (Leveling Valve Type)	032-55-001	
D4 Intake Filter	032-11-033	1
D4 Comp. Brushes	032-11-251	
Interlock Arm Contacts	035-01-191	
Cam Switch Tip, Moveable	035-80-001	6
Cam Switch Tip, Fixed	035-90-002	6
Contact Tip, Copper	035-80-005	
Contact Tip, Silver	035-65-319	
Cam Switch Shunts	035-01-154	
Line Switch Tip	035-01-105	2
E-Brake Lever Plastic Tab	026-96-115	
Bearing Temperature Tags	024-03-030	
Enter Stock no. and Qty. into Work Order via Scan Tool		

DEFERRED ITEMS LIST

Work Order ID: 432-2021-8189

Mileage Since Last Inspected: 7902

Deferred Priority Codes: A-Hold for Repair, B-Schedule for Repair

[illegible]

#1 Wheel Size: 27 1/2 Condition: Minor Spalls #2 Wheel Size: 27 1/2 Condition: Minor Spalls
#3 Wheel Size: 28 Condition: Minor Spalls #4 Wheel Size: 27 1/2 Condition: Minor Spalls

Foreperson's Signature PII Employee Number: 69457

Initial Sections 2.d,e,f. and 10.p.

EQUAL ACCESS INSPECTION

RED LINE FLEET

DATE: 10/21/21

CAR NUMBER: 1757

Platform Height and Gap Inspection

Place threshold gauge onto and inside the running rail, keeping gauge level to floor. Use gauge to inspect door threshold height and gap by using the colors on the measurement-sliding device. Green area inspects the gap, red area inspects the height.

DOOR	PLATFORM GAP MEASUREMENT		PLATFORM HEIGHT MEASUREMENT	
	GO	NO GO	GO	NO GO
A	✓		✓	
B	✓		✓	
C	✓		✓	
D	✓		✓	
E	✓		✓	
F	✓		✓	
G				
H				

PA Sound Level Inspection

Place the sound level meter in the center of the car, five feet above floor for test. Activate door close chime, recording the maximum (dBA) level on the meter.

Maximum level recorded (dBA) 78

Enter Y-EAI code and 30 minutes labor on each car, file with Mileage Inspection sheet.

MBTA REDLINE

#1 and #2 CAR

CAR NO. 01757DATE: 12/20/21**INSPECTION FORM**MILEAGE SINCE LAST INSPECTED: 7725

Tasks:	V-Visual	L-Lubricate	C-Clean
	F-Verify proper function	R-Replace as needed	P-Purge
	A-Adjust to proper setting	X-Record values	T-Test

Note to Inspection Staff: If any problems are noted during your inspection please place a circle around the task number of the problem area. These circled items will then be transferred to deferred items list for further attention.

Task No.	Description	Task	Initials	Task No.	Description	Task	Initials
Truck Inspection Sections 1,2,3				Truck Inspector Initial Sections 1,2,3			
1	Truck Frame	V	PII	Signature: <u>PII</u> Emp. No: <u>497354</u>			
1.a	King Pin and Hardware	V,F		Propulsion Section 4			
1.b	Hoses, Piping and Clamps	V,F		4	Propulsion Enclosure, Covers, Gaskets	V,F,C	PII
1.c	Cables, Ground Straps	V,F,R		4.a	Propulsion Relays and Tips	V,F,C,R	
1.d	Bearer Surfaces ; Center and Side	V,F		4.b	Cables, Wiring, Connections	V,F,A	
1.e	Journal Springs	V		4.c	Line Switch Coil-Blowout, Overload	V,F,A,R,C	
1.f	Pedestal Bolts	V,A		4.d	Line Switch Tips-Main, Overload	V,F,A,R,C	
1.g	Bolster Anchors Shimming and Bolts	V,F		4.e	Operation of all Mag Valves	V,F,L	
1.h	Dampers, Snubbers and Shocks	V,F		4.f	SPC Tips, Cam Rollers, Shunts	V,F,A,R,C	
1.i	Hand Brake Linkage	V,F,A,L,R		4.g	SPC Interlock Tips	V,F,A,R,C	
1.j	Shoe Beams, Flash Shields (hardware)	V,F,A		4.h	PBC Tips, Cam Rollers, Shunts	V,F,A,R,C	
1.k	Collector Paddles (height and tension)	V,F,A,R		4.i	Reverser Segments and Insulators	V,F,R,C	
1.l	Shoe Shunts, Fuses and Hardware	V,F,A,R		4.j	Reverser Interlock Tips	V,F,A,R,C	
1.m	Sleet Scrapers, Blades, Hoses and Hardware	V,F,A,L,R		4.k	Contactor Tips and Shunts	V,F,A,R,C	
1.n	Trips, Hoses and Hardware	V,F,A,L		4.l	Contactor Interlock Tips, Shunts, Arms	V,F,A,R,C	
1.o	Brake Units, Shoes, Keys, Piping and Hoses	V,F,A,L,R		4.m	Electronic Cards	V,F,R	
1.p	Brake Cutout, Linkage and Hardware	V,F,L		4.n	Cam Controller, Switches, Tips and Shunts	V,F,A,R,C	
1.q	ATP Receiver Coils and Hardware	V,C		4.o	Mag Amp Wiring and Connections	V,F	
Gear Units				4.p	Field Forcing Panel, Fuse, Wiring	V,F	
2	Gears	V		4.q	Field Shunt Resistors, Fuse, Wiring	V,F,R	
2.a	Gear Oil	V,R		4.r	Inshot Valve Operation	V,F,A	
2.b	Covers, Plugs and Breathers	V,C		4.s	Propulsion Ground Fault Unit (#1 Car)	V,F,R	
2.c	Bearings, Wear Plates, Temperature Tag	V,L,R		4.t	Propulsion Overload Light	V,F,R	
2.d	Wheels	V		4.u	Propulsion Megger Reading	V,F,X	
2.e	Wheel Flanges (gauge)	V		Case: <u>07</u> Meg Ω			
2.f	Wheel Diameter	V,X		4.v	Contact Shoe Megger Reading	V,F,X	
2.g	Axles (Wheel Back to Back Measurement)	V,X		Shoe: <u>00</u> Meg Ω			
	1: <u>53 3/8</u> 2: <u>53 3/8</u>			4.w	Braking Grids and Cables	V	
	3: <u>53 3/8</u> 4: <u>53 3/8</u>			4.x	Propulsion Air Supply, Hoses and Piping	V,F	
2.h	Axle Ground Brushes and Springs	V,F,R		4.y	Sequence Controls With Box and Cineston	V,F	
2.i	Axle Ground Ring	V		4.z	Notch car with 600v "Think Safety"	V,F	
	Signature: <u>PII</u>			Propulsion Inspector Initial Section 4			
2.j	Axle Ground Housings and Hardware	V,F,R		Signature: <u>PII</u> Emp. No: <u>71590</u>			
2.k	Axle Ground Cables Straps and Jumpers	V,F,A,R		Air & Electric / Couplers Inspection Sections 5,6,7			
Traction Motors				5	Air System	V	PII
3	Motors	V		5.a	Compressor Motor Brushes	V,F,C,R	
3.a	Motor Filters, Covers	V,F,R		5.b	Air Compressor Unit, Oil Level	V,F,L,R	
3.b	Motor Brushes, Brush holders	V,F,R		5.c	Compressor Control Box and Tips	V,F,R	
3.c	Horizontal Mounting Bolts and Bushings	V					
3.d	Vertical Mounting Bolts and Bushings	V					
3.e	Safety Brackets and Hardware	V,F					
3.f	Motor to Gear Unit Bolts (torque) 150 ft-lbs.	V,A					
3.g	Motor Cables and Clamps	V,F					
3.h	Motor Clamshell Leads	V					
3.i	Clamshell Contacts and Hardware	V					

Task No.	Description	Task	Initials	Task No.	Description	Task	Initials	
Air & Electric / Couplers (continued)				Car Body Inspection Sections 8,9,10				
5d.	Gov. Pressure Switch; Gov. Off/On PSI <u>150</u> / <u>134</u>	V,F,A,X	PII	Interior				
5.e.	Compressor Off Time: <u>3</u> min <u>34</u> sec	V,F,X		8	Interior Car body	V	PII	
5.f.	Intercooler Pressure: <u>41</u> PSI	V,F,X,P		8.a.	Glass and Window Gaskets	V,F,R		
5.g.	Drain Valve / Tanks (purge)	V,F,P		8.b.	Lighting; Passenger, Cab, Emergency	V,F,R		
5.h.	Heaters (compressor and drain valve)	V,F		8.c.	Horns, Buzzers and Bells	V,F		
5.i.	Wiring, Piping, Hoses	V,F		8.d.	Windshield Wiper and Blade	V,F,R		
5.j.	Dryers / Filters	V,F		8.e.	Cab Heat and Defroster	V,F,C		
5.k.	Cineston and Deadman Operation, Switch Springs, Cineston Contact Tips	V,F,C,R		8.f.	Radio, PA, Intercom and PEI	V,F		
5.l.	Console Gauges	V,F,A,R		8.g.	Operator's Seat, Visor and Curtains	V,F,R		
5.m.	Brake Pressures: Brake Valves SAP <u>72</u> PSI BP <u>110</u> PSI MIN <u>16</u> PSI MAX <u>38</u> PSI EMERG <u>46</u> PSI SNOW <u>9</u> PSI INSHOT <u>9</u> PSI	V,F,A,X		8.h.	Sash Windows	V,F,R		
5.n.	Air Spring /Leveling Valves, Pressures #1 <u>22</u> PSI #2cs <u>24</u> PSI #2ocs <u>22</u> PSI	V,F,A,X		8.i.	Console Switches and Labels	V,F,R		
Auxiliary Electrics				8.j.	Instruction Decals and Advertising Signs	V,F		
6	Converter: Gaskets, Covers, Hardware	V,F		8.k.	Safety Equipment: Ladder, 4 Shoe Hooks, Shoe Lifter, 2 Fire Extinguishers, Evac Chair/even car, Rope/Ty-Rap®	V,F,R		
6.a.	Electronic Card Rack / Controls	V,F		8.l.	Low Voltage Circuit Breaker Panel	V		
6.b.	External Resistors: Cabling	V		8.m.	Stanchions and Grab Handles	V,F		
6.c.	Output Voltage MG / Converter <u>37.6</u> volts.	V,F,A,X	8.n.	Passenger Seats	V,R			
6.d.	Battery Enclosure, Cover, Hardware	V,F,C	8.o.	Passenger Emergency Pulls and Tabs	V,F,R			
6.e.	Battery Vent Caps, Terminals, Cables, Trays	V,F,C	8.p.	Interior Panels and Flooring	V			
6.f.	Battery Cells, Excessive Corrosion	V,F,R,C	8.q.	Trip Cutout, Horn Cutout and Air Spring Cutouts	V,F			
6.g.	Battery Electrolyte Level (deionized water) Battery <u>32.4</u> volts.	V,F,R,X	8.r.	Handbrake Ratchet and Micro Switch	V,F,L			
6.h.	Snow Brake, Sleet Scraper (amber) Lights	V,F,R	8.s.	Destination Signs and Lighting	V,F,R			
Couplers				Exterior				
7	Electric Coupler Boxes and Buttons	V,F,R,C	9	Exterior Car body	V			
7.a.	Air Control Valves (EP Box)	V,F	9.a.	Destination Signs Roll; Interior / Exterior	V,F,R			
7.b.	Centering Device and Negating Valve	V,F,L	9.b.	Marker Lights	V,F,R			
7.c.	Drum Switch	V,F	9.c.	ATP Operation (amber) Lights	V,F,R			
7.d.	Draft Gears	V,F	9.d.	Snow brake / Sleet Scraper (amber) Lights	V,F,R			
7.e.	Coupler Head, Height Adjuster, Gauge	V,F,L	9.e.	End Gate, Springs and Straps	V,F			
7.f.	Manual Uncouple Lever	V,F,L	9.f.	Handbrake, Door Pilot, and Individual Door Leaf Lights	V,F,R			
7.g.	Drawbar Yoke, Anchor and Casting	V,F	Doors					
7.h.	Shear Pins and Safety Wire	V,R	10	Door Operation	V,F			
7.i.	Radial Carrier	V,F,L	10.a.	Door Control Relay Panel; Relays & Wiring	V,F,C,R			
7.j.	Cables, Clamps, Cannon Plugs (safety wire)	V,R	10.b.	Door Open & Close Toggle Switches	V,F,R			
7.k.	Air Pipes, Hoses, Clamps and Hardware	V,R	10.c.	Door Set-up Switch	V,F			
Air & Electric / Couplers Inspector Initial Section 5,6,7				10.d.	Door By-Pass Switch	V,F		
Signature: <u>PII</u> Emp. No: <u>73560</u>				10.e.	Door Engine Operators	V,F,A		
				10.f.	Obstruction Micro Switches	V,F,A		
				10.g.	Door Locking / Unlocking Assemblies	V,F,A,L		
				10.h.	Door Obstruction; Test Top, Middle and Bottom	V,F,A		
				10.i.	Door Leaf Alignment	V,F,A		
				10.j.	Door Actuators, Tracks, Rollers and Shims	V,F		
				10.k.	Door Nosing Rubbers, Alignment, Gap and Condition	V,F,A		
				10.l.	Door Emergency Release Handles	V,F,A		
				10.m.	#1 End Door (track, lock and latch)	V,F,L,C		
				10.o.	Cab Door (jamb, hinges and lock)	V,F,L,C		
				10.p.	Spin Slide System	V,F		

Task No.	Description	Task	Initials
Doors (Continued)			
10.q.	Door Safety Ground Test: Pin #19: <u>26</u> Ω Pin #20: <u>26</u> Ω	V,F,X	PII
10.r.	No Motion Sensors B-C AXLE 1: <u>425</u> Ω AXLE 2: <u>435</u> Ω AXLE 3: <u>431</u> Ω E-F AXLE 4: <u>434</u> Ω	V,F,X	
10.s.	ATO Readings ASR: <u>N/A</u> Ω FRG: <u>N/A</u> Ω Receiver Coil Reading: <u>N/A</u> Ω	V,F,X	
Equal Access Inspection			
11	Complete Per Procedure Using EAI Form Filed With This Mileage Inspection Form	T	
Car Body Inspector Initial Sections 8,9,10,11			
Signature: <u>PII</u> Emp. No: <u>70815</u>			

Part	Stock Number	Quantity
Contact Shoe	025-96-001	1
Contact Shoe Shunt	025-74-090	
Contact Shoe Stud	025-96-010	
Ice Scraping Contact Shoe	030-74-118	1
Shoe Fuse #1&2 Car	025-74-509	
Brake Shoe #1&2 Car	010-96-029	2
Sleet Scraper Blade	025-97-001	
Sleet Scraper Blade	025-97-002	
Ground Brush Holder #1&2 Car	033-74-010	
Ground Brush #1&2 Car	035-74-277	2
Ground Brush Spring #1&2 Car	033-74-007	
Ground Brush Holder Insert #1&2 Car	033-74-008	
Ground Brush Cover #1&2 Car	035-07-167	
Traction Motor Filter	030-80-132	86
Traction Motor Brush	025-04-240	8
Hitch Pin, (Handbrake Type)	420-71-020	
Picture Window	023-11-285	
Stationary Sash Window, #1 Car	023-11-314	
Sliding Sash Window, #1 Car	023-11-315	
Stationary Sash Window, #2 Car	026-74-055	
Sliding Sash Window, #2 Car	026-74-056	
Door Glass	023-11-295	
Fire Extinguisher, 10 lb.	024-10-078	
Fire Extinguisher, 20 lb.	024-10-075	
Frangible Pins, #1 Car	034-96-131	
Frangible Pins, #2 Car	026-74-001	
Fluorescent Tube T-12 48"	311-55-654	
Lamp Ballast	025-74-113	
Fluorescent Tube T-12 36"	311-55-643	
Fluorescent Tube T-12 18"	311-55-608	
Fluorescent Tube T-12 24"	311-55-615	
Pilot Light, Double Contact	025-45-837	
Pilot Light, Single Contact	025-45-022	
Bulb, Duplex Gauge	025-45-849	
Shatterproof Air Gauge Lens	032-28-046	
Drawbar Button # 1 Car	026-96-500	
Drawbar Button # 2 Car	025-23-023	
Hitch Pin (Leveling Valve Type)	032-55-001	
D4 Intake Filter	032-11-033	1
D4 Comp. Brushes	032-11-251	
Interlock Arm Contacts	035-01-191	
Cam Switch Tip, Moveable	035-80-001	10
Cam Switch Tip, Fixed	035-90-002	10
Contact Tip, Copper	035-80-005	
Contact Tip, Silver	035-65-319	
Cam Switch Shunts	035-01-154	
Line Switch Tip	035-01-105	2
E-Brake Lever Plastic Tab	026-96-115	
Bearing Temperature Tags	024-03-030	
035-01-051		1
Enter Stock no. and Qty. into Work Order via Scan Tool		

Work Order ID: 432-2621-10281

Mileage Since Last Inspected: 7725

EQUAL ACCESS INSPECTION

RED LINE FLEET

DATE: 12/20/21

CAR NUMBER: 01757

Platform Height and Gap Inspection

Place threshold gauge onto and inside the running rail, keeping gauge level to floor. Use gauge to inspect door threshold height and gap by using the colors on the measurement-sliding device. Green area inspects the gap, red area inspects the height.

DOOR	PLATFORM GAP MEASUREMENT		PLATFORM HEIGHT MEASUREMENT	
	GO	NO GO	GO	NO GO
A	✓		✓	
B	✓		✓	
C	✓		✓	
D	✓		✓	
E	✓		✓	
F	✓		✓	
G	X	X	X	X
H	X	X	X	X

PA Sound Level Inspection

Place the sound level meter in the center of the car, five feet above floor for test. Activate door close chime, recording the maximum (dBA) level on the meter.

Maximum level recorded (dBA) 79

Enter Y-EAI code and 30 minutes labor on each car, file with Mileage Inspection sheet.

MBTA REDLINE
#1 and #2 CAR

CAR NO. 1757


DATE: 2/2/12

INSPECTION FORM

MILEAGE SINCE LAST INSPECTED: 7802

Tasks:	V-Visual	L-Lubricate	C-Clean
	F-Verify proper function	R-Replace as needed	P-Purge
	A-Adjust to proper setting	X-Record values	T-Test

Note to Inspection Staff: If any problems are noted during your inspection please place a circle around the task number of the problem area. These circled items will then be transferred to deferred items list for further attention.

Task No.	Description	Task	Initials	Task No.	Description	Task	Initials
Truck Inspection Sections 1,2,3				Truck Inspector Initial Sections 1,2,3			
1	Truck Frame	V	PII	 Signature: _____ Emp. No: <u>72244</u>			
1.a	King Pin and Hardware	V,F					
1.b	Hoses, Piping and Clamps	V,F					
1.c	Cables, Ground Straps	V,F,R					
1.d	Bearer Surfaces ; Center and Side	V,F					
1.e	Journal Springs	V		Propulsion Section 4			
1.f	Pedestal Bolts	V,A		4	Propulsion Enclosure, Covers, Gaskets	V,F,C	PII
1.g	Bolster Anchors Shimming and Bolts	V,F		4.a	Propulsion Relays and Tips	V,F,C,R	
1.h	Dampers, Snubbers and Shocks	V,F		4.b	Cables, Wiring, Connections	V,F,A	
1.i	Hand Brake Linkage	V,F,A,L,R		4.c	Line Switch Coil-Blowout, Overload	V,F,A,R,C	
1.j	Shoe Beams, Flash Shields (hardware)	V,F,A		4.d	Line Switch Tips-Main, Overload	V,F,A,R,C	
1.k	Collector Paddles (height and tension)	V,F,A,R		4.e	Operation of all Mag Valves	V,F,L	
1.l	Shoe Shunts, Fuses and Hardware	V,F,A,R		4.f	SPC Tips, Cam Rollers, Shunts	V,F,A,R,C	
1.m	Steel Scrapers, Blades, Hoses and Hardware	V,F,A,L,R		4.g	SPC Interlock Tips	V,F,A,R,C	
1.n	Trips, Hoses and Hardware	V,F,A,L		4.h	PBC Tips, Cam Rollers, Shunts	V,F,A,R,C	
1.o	Brake Units, Shoes, Keys, Piping and Hoses	V,F,A,L,R		4.i	Reverser Segments and Insulators	V,F,R,C	
1.p	Brake Cutout, Linkage and Hardware	V,F,L		4.j	Reverser Interlock Tips	V,F,A,R,C	
1.q	ATP Receiver Coils and Hardware	V,C		4.k	Contactor Tips and Shunts	V,F,A,R,C	
Gear Units				4.l	Contactor Interlock Tips, Shunts, Arms	V,F,A,R,C	
2	Gears	V		4.m	Electronic Cards	V,F,R	
2.a	Gear Oil	V,R		4.n	Cam Controller, Switches, Tips and Shunts	V,F,A,R,C	
2.b	Covers, Plugs and Breathers	V,C		4.o	Mag Amp Wiring and Connections	V,F	
2.c	Bearings, Wear Plates, Temperature Tag	V,L,R		4.p	Field Forcing Panel, Fuse, Wiring	V,F	
2.d	Wheels	V		4.q	Field Shunt Resistors, Fuse, Wiring	V,F,R	
2.e	Wheel Flanges (gauge)	V		4.r	Inshot Valve Operation	V,F,A	
2.f	Wheel Diameter	V,X		4.s	Propulsion Ground Fault Unit (#1 Car)	V,F,R	
2.g	Axles (Wheel Back to Back Measurement)	V,X		4.t	Propulsion Overload Light	V,F,R	
	1: <u>538</u> 2: <u>538</u>			4.u	Propulsion Megger Reading	V,F,X	
	3: <u>538</u> 4: <u>538</u>				Case: <u>6</u> Meg Ω		
2.h	Axle Ground Brushes and Springs	V,F,R		4.v	Contact Shoe Megger Reading	V,F,X	
2.i	Axle Ground Rigs	V			Shoe: <u>800+</u> Meg Ω		
	Signature: 			4.w	Braking Grids and Cables	V	
2.j	Axle Ground Housings and Hardware	V,F,R		4.x	Propulsion Air Supply, Hoses and Piping	V,F	
2.k	Axle Ground Cables Straps and Jumpers	V,F,A,R		4.y	Sequence Controls With Box and Cineston	V,F	
Traction Motors				4.z	Notch car with 600v "Think Safety"	V,F	
3	Motors	V		Propulsion Inspector Initial Section 4			
3.a	Motor Filters, Covers	V,F,R		 Signature: _____ Emp. No: <u>66311</u>			
3.b	Motor Brushes, Brush holders	V,F,R					
3.c	Horizontal Mounting Bolts and Bushings	V					
3.d	Vertical Mounting Bolts and Bushings	V					
3.e	Safety Brackets and Hardware	V,F					
3.f	Motor to Gear Unit Bolts (torque) 150 ft-lbs.	V,A		Air & Electric / Couplers Inspection Sections 5,6,7			
3.g	Motor Cables and Clamps	V,F		5	Air System	V	PII
3.h	Motor Clamshell Leads	V		5.a	Compressor Motor Brushes	V,F,C,R	
3.i	Clamshell Contacts and Hardware	V		5.b	Air Compressor Unit, Oil Level	V,F,L,R	
				5.c	Compressor Control Box and Tips	V,F,R	

Task No.	Description	Task	Initials	Task No.	Description	Task	Initials
Air & Electric / Couplers (continued)				Car Body Inspection Sections 8,9,10			
5d.	Gov. Pressure Switch; Gov. Off/On PSI <u>130</u> / <u>150</u>	V,F,A,X	PII	Interior			
5.e.	Compressor Off Time: <u>7</u> min <u>60</u> sec	V,F,X		8	Interior Car body	V	PII
5.f.	Intercooler Pressure: <u>42</u> PSI	V,F,X,P		8.a.	Glass and Window Gaskets	V,F,R	
5.g.	Drain Valve / Tanks (purge)	V,F,P		8.b.	Lighting; Passenger, Cab, Emergency	V,F,R	
5.h.	Heaters (compressor and drain valve)	V,F		8.c.	Horns, Buzzers and Bells	V,F	
5.i.	Wiring, Piping, Hoses	V,F		8.d.	Windshield Wiper and Blade	V,F,R	
5.j.	Dryers / Filters	V,F		8.e.	Cab Heat and Defroster	V,F,C	
5.k.	Cineston and Deadman Operation, Switch Springs, Cineston Contact Tips	V,F,C,R		8.f.	Radio, PA, Intercom and PEI	V,F	
5.l.	Console Gauges	V,F,A,R		8.g.	Operator's Seat, Visor and Curtains	V,F,R	
5.m.	Brake Pressures: Brake Valves SAP <u>70</u> PSI BP <u>110</u> PSI MIN <u>14</u> PSI MAX <u>39</u> PSI EMERG <u>45</u> PSI SNOW <u>8</u> PSI INSHOT <u>10</u> PSI	V,F,A,X		8.h.	Sash Windows	V,F,R	
5.n.	Air Spring /Leveling Valves, Pressures #1 <u>21</u> PSI #2cs <u>20</u> PSI #2ocs <u>20</u> PSI	V,F,A,X	8.i.	Console Switches and Labels	V,F,R		
Auxiliary Electrics				8.j.	Instruction Decals and Advertising Signs	V,F	
6	Converter: Gaskets, Covers, Hardware	V,F	8.k.	Safety Equipment: Ladder, 4 Shoe Hooks, Shoe Lifter, 2 Fire Extinguishers, Evac Chair/even car, Rope/Ty-Rap®	V,F,R		
6.a.	Electronic Card Rack / Controls	V,F	8.l.	Low Voltage Circuit Breaker Panel	V		
6.b.	External Resistors: Cabling	V	8.m.	Stanchions and Grab Handles	V,F		
6.c.	Output Voltage <u>37.60</u> MG / Converter <u>37.60</u> volts.	V,F,A,X	8.n.	Passenger Seats	V,R		
6.d.	Battery Enclosure, Cover, Hardware	V,F,C	8.o.	Passenger Emergency Pulls and Tabs	V,F,R		
6.e.	Battery Vent Caps, Terminals, Cables, Trays	V,F,C	8.p.	Interior Panels and Flooring	V		
6.f.	Battery Cells, Excessive Corrosion	V,F,R,C	8.q.	Trip Cutout, Horn Cutout and Air Spring Cutouts	V,F		
6.g.	Battery Electrolyte Level (deionized water) Battery <u>32.42</u> volts.	V,F,R,X	8.r.	Handbrake Ratchet and Micro Switch	V,F,L		
6.h.	Snow Brake, Sleet Scraper (amber) Lights	V,F,R	8.s.	Destination Signs and Lighting	V,F,R		
Couplers				Exterior			
7	Electric Coupler Boxes and Buttons	V,F,R,C	9	Exterior Car body	V		
7.a.	Air Control Valves (EP Box)	V,F	9.a.	Destination Signs Roll; Interior / Exterior	V,F,R		
7.b.	Centering Device and Negating Valve	V,F,L	9.b.	Marker Lights	V,F,R		
7.c.	Drum Switch	V,F	9.c.	ATP Operation (amber) Lights	V,F,R		
7.d.	Draft Gears	V,F	9.d.	Snow brake / Sleet Scraper (amber) Lights	V,F,R		
7.e.	Coupler Head, Height Adjuster, Gauge	V,F,L	9.e.	End Gate, Springs and Straps	V,F		
7.f.	Manual Uncouple Lever	V,F,L	9.f.	Handbrake, Door Pilot, and Individual Door Leaf Lights	V,F,R		
7.g.	Drawbar Yoke, Anchor and Casting	V,F	Doors				
7.h.	Shear Pins and Safety Wire	V,R	10	Door Operation	V,F		
7.i.	Radial Carrier	V,F,L	10.a.	Door Control Relay Panel; Relays & Wiring	V,F,C,R		
7.j.	Cables, Clamps, Cannon Plugs (safety wire)	V,R	10.b.	Door Open & Close Toggle Switches	V,F,R		
7.k.	Air Pipes, Hoses, Clamps and Hardware	V,R	10.c.	Door Set-up Switch	V,F		
Air & Electric / Couplers Inspector Initial Section 5,6,7				10.d.	Door By-Pass Switch	V,F	
Signature: <u>[Signature]</u> No: <u>73601</u>				10.e.	Door Engine Operators	V,F,A	
				10.f.	Obstruction Micro Switches	V,F,A	
				10.g.	Door Locking / Unlocking Assemblies	V,F,A,L	
				10.h.	Door Obstruction; Test Top, Middle and Bottom	V,F,A	
				10.i.	Door Leaf Alignment	V,F,A	
				10.j.	Door Actuators, Tracks, Rollers and Shims	V,F	
				10.k.	Door Nosing Rubbers, Alignment, Gap and Condition	V,F,A	
				10.l.	Door Emergency Release Handles	V,F,A	
				10.m.	#1 End Door (track, lock and latch)	V,F,L,C	
					#2		
				10.o.	Cab Door (jamb, hinges and lock)	V,F,L,C	
				10.p.	Spin Slide System	V,F	

Task No.	Description	Task	Initials
Doors (Continued)			
10.q.	Door Safety Ground Test: Pin #19: <u>1</u> Ω Pin #20: <u>12</u> Ω	V,F,X	PII
10.r.	No Motion Sensors B-C AXLE 1: <u>423</u> Ω AXLE 2: <u>423</u> Ω AXLE 3: <u>424</u> Ω E-F AXLE 4: <u>423</u> Ω	V,F,X	
10.s.	ATO Readings ASR: <u>✓</u> Ω FRG: <u>✓</u> Ω Receiver Coil Reading: <u>✓</u> Ω	V,F,X	
Equal Access Inspection			
11	Complete Per Procedure Using EAI Form Filed With This Mileage Inspection Form	T	
Car Body Inspector Initial Sections 8,9,10,11			
Signature: <u>PII</u> Emp. No: <u>66422</u>			

Part	Stock Number	Quantity
Contact Shoe	025-96-001	
Contact Shoe Shunt	025-74-090	
Contact Shoe Stud	025-96-010	
Ice Scraping Contact Shoe	030-74-118	
Shoe Fuse #1&2 Car	025-74-509	
Brake Shoe #1&2 Car	010-96-029	6
Sleet Scraper Blade	025-97-001	
Sleet Scraper Blade	025-97-002	
Ground Brush Holder #1&2 Car	033-74-010	
Ground Brush #1&2 Car	035-74-277	6
Ground Brush Spring #1&2 Car	033-74-007	
Ground Brush Holder Insert #1&2 Car	033-74-008	
Ground Brush Cover #1&2 Car	035-07-167	
Traction Motor Filter	030-80-132	16
Traction Motor Brush	025-04-240	4
Hitch Pin, (Handbrake Type)	420-71-020	
Picture Window	023-11-285	
Stationary Sash Window, #1 Car	023-11-314	
Sliding Sash Window, #1 Car	023-11-315	
Stationary Sash Window, #2 Car	026-74-055	
Sliding Sash Window, #2 Car	026-74-056	
Door Glass	023-11-295	
Fire Extinguisher, 10 lb.	024-10-078	1
Fire Extinguisher, 20 lb.	024-10-075	
Frangible Pins, #1 Car	034-96-131	
Frangible Pins, #2 Car	026-74-001	
Fluorescent Tube T-12 48"	311-55-654	
Lamp Ballast	025-74-113	
Fluorescent Tube T-12 36"	311-55-643	
Fluorescent Tube T-12 18"	311-55-608	
Fluorescent Tube T-12 24"	311-55-615	
Pilot Light, Double Contact	025-45-837	1
Pilot Light, Single Contact	025-45-022	
Bulb, Duplex Gauge	025-45-849	
Shatterproof Air Gauge Lens	032-28-046	
Drawbar Button # 1 Car	026-96-500	
Drawbar Button # 2 Car	025-23-023	
Hitch Pin (Leveling Valve Type)	032-55-001	
D4 Intake Filter	032-11-033	
D4 Comp. Brushes	032-11-251	
Interlock Arm Contacts	035-01-191	
Cam Switch Tip, Moveable	035-80-001	2
Cam Switch Tip, Fixed	035-90-002	2
Contact Tip, Copper	035-80-005	
Contact Tip, Silver	035-65-319	
Cam Switch Shunts	035-01-154	
Line Switch Tip	035-01-105	2
E-Brake Lever Plastic Tab	026-96-115	
Bearing Temperature Tags	024-03-030	
Enter Stock no. and Qty. into Work Order via Scan Tool		

DEFERRED ITEMS LIST

Mileage Since Last Inspected: 7802

EQUAL ACCESS INSPECTION

RED LINE FLEET

DATE: 2/2/22

CAR NUMBER: 1757

Platform Height and Gap Inspection

Place threshold gauge onto and inside the running rail, keeping gauge level to floor. Use gauge to inspect door threshold height and gap by using the colors on the measurement-sliding device. Green area inspects the gap, red area inspects the height.

DOOR	PLATFORM GAP MEASUREMENT		PLATFORM HEIGHT MEASUREMENT	
	GO	NO GO	GO	NO GO
A	✓		✓	
B	✓		✓	
C	✓		✓	
D	✓		✓	
E	✓		✓	
F	✓		✓	
G				
H				

PA Sound Level Inspection

Place the sound level meter in the center of the car, five feet above floor for test. Activate door close chime, recording the maximum (dBA) level on the meter.

Maximum level recorded (dBA) 90

Enter Y-EAI code and 30 minutes labor on each car, file with Mileage Inspection sheet.

